

# **Certes Networks CEP10-R**

FIPS Validated 10 Mbps Network Encryptor

# **Product Overview**

The CipherEngine Enforment Point (CEP) is a flexible encryption appliance providing Ethernet frame encryption for Layer 2 Ethernet networks, IP packet encryption for Layer 3 networks and Layer 4 data payload encryption for IP and MPLS networks. The CEP10-R offers full-duplex line rate encryption at 10 Mbps (20 Mbps aggregated), using the AES 256 bit encryption algorithm.

The CEP10-R enables organizations to standardize on one platform for small or remote branch office networks. The CEPs integrate easily into any existing network, operating transparently to the network and ensuring all of your data transmissions are encrypted.

# Scalable and Secure Group Encryption

The CEP10-R uses scalable group encryption to provide encrypted and authenticated lowlatency any-to-any connectivity. The CEP10-R uses Certes Networks' centralized management solution (CipherEngine) to securely generate and distribute group keys to authorized endpoints. By avoiding the use of tunnels, group encryption greatly reduces deployment complexity and provides fully-meshed encryption that is easy to manage.

#### **Ethernet Frame Encryption**

The CEP10-R is compatible with all multipoint-to-multipoint Ethernet, point-to-point Ethernet, and Layer 2 multicast or unicast topologies. As part of the encryption process with the CEPs, each and every Ethernet frame is authenticated. The CEPs can encrypt all Ethernet frames or encrypt selectively based on VLAN ID.

# **IP Packet Encryption**

Using IP Security protocol (IPsec), the CEP10-R provides full data encryption for Layer 3 IP networks at 10 Mbps (20 Mbps aggregated). The CEP10-R IP packet encryption works with IP and MPLS IP-VPN networks. The CEP10-R supports the CipherEngine Encapsulating Security Payload protocol (CE-ESP) to preserve the original IP packet header and encrypt just the payload. This unique functionality maintains network transparency, while providing maximum data protection. By preserving the original header information and encrypting only the payload, the CEP10-R can protect data over any IP network infrastructure including multicarrier, load-balanced and high availability networks.

# **Payload Only Encryption**

In addition to standard IPsec encryption, (which encrypts the Layer 4 header), the CEP10-R offers a Layer 4 compatible "payload only" encryption option. This unique, patent-pending capability allows network services, such as Netflow/Jflow, and Class of Service (CoS) based traffic shaping and Network Address Translation (NAT) to be maintained through the service provider network while the payload itself is encrypted.

# **Central Policy Management**

The CEP10-R can be configured and centrally managed via the CipherEngine Policy and Key Manager. CipherEngine allows both Security and Network Administrators to quickly and easily manage network security from a centralized interface with simple drag and drop functionality.

Encryption policies can be based on source or destination IP addresses, source or destination port numbers, protocol IDs, or VLAN tags. Policies can be quickly and easily modified in seconds on even the largest networks, without traffic disruptions or interaction with remote personnel. CipherEngine also provides logging and audit mechanisms to meet or exceed compliance and audit requirements.



# PRODUCT SNAPSHOT

- FIPS 140-2 Level 2 validated
- Wire-rate encrypted throughput at 10 Mbps (full duplex)
- Layer 2 Ethernet frame, Layer 3 IP packet, and Layer 4 payload protection
- Per-Frame/Packet
  Authentication
- Preserves VLAN and MPLS
  tags

# FEATURES AND BENEFITS

- Transparent to network and applications
- Seamless scalability
- Infrastructure neutral
- Easy installation and management
- Create secure network
  groups

#### COMPREHENSIVE DATA PROTECTION

- IPsec site-to-site networks
- MPLS meshed networks
- Metro Ethernet and VPLS
  networks
- Voice and Video over IP
  applications
- Multicast streams



# Certes Networks CEP10-R

FIPS Validated 10Mbps Network Encryptor

# **Encrypted Throughput**

• 10 Mbps (full duplex)

# Encryption Support • AES 256

# Authentication and Integrity

• HMAC-SHA-1-96

# **Network Support**

- Ethernet
- VLAN tag preservation
- MPLS tag preservation
- IPv4
- IPv6 (Layer 2 Ethernet encryption mode)
- Multicast streams
- NTP

# **Policy Selector Options**

- Source or destination IP address
- Source or destination port number
- Protocol ID (L3 and L4 options)
- VLAN ID (L2 option)
- Multicast address

# Transforms

- CipherEngine ESP Tunnel Mode (header preservation option)
- CipherEngine ESP Transport Mode (L4 option)
- CipherEngine Ethernet ESP Mode

# **Device Management**

- CipherEngine
- Command Line Interface
- Out-of-band management
- Alarm condition detection and reporting
- Syslog support
- SNMPv2c and SNMPv3 managed object support
- Audit Log

# Regulatory

- Safety: UL 60950-1
- Emissions f FCC part 15 subpart B class A

# Management Communication Security Options

- X.509 v3 digital certificates
- TLS (full authentication)
- SSH
- IKE/IPsec

# **Environmental**

- Operating temperature: 0° to 40° C (32° to 104° F)
- EU WEEE
- FU RoHS-5

# Indicators

- Power
- Alarm
- LED Status

# Physical

- 1U tamper evident chassis
- Dimensions: 1.6"H x 8.0"W x 5.8"D
- Rack mountable in standard 19" rack or desktop option
- External Power Adapter: 100-240V A/C @ 1.5A, 50/60Hz, output 12V D/C, 5A max (60W max)
- Thermal: In-rush 102 BTU/hr, Steady-state 102 BTU/hr
- Nominal input current: 0.25A
- Weight: 3 lbs as rackmount; 1 lb., 5 oz. as desktop
- MTBF: 388,999 hours

# Interfaces

- Data: Two 10/100/1000 RJ45 Ethernet ports
- Management: One 10/100 RJ45 Ethernet and one RS232 serial port
- Aux1 RJ45 port is for future use

# **Global Headquarters**

300 Corporate Center Dr., Suite 140 Pittsburgh, PA 15108 Tel: +1 (888) 833-1142 Fax: +1 (412) 262-2574 www.CertesNetworks.com sales@certesnetworks.com

EMEA Sales emea@certesnetworks.com Asia-Pacific Sales apac@certesnetworks.com Government Sales fedsales@certesnetworks.com