



# VMware vSphere™ 4.1 Security Hardening Guide

Rev C: June 2011

TECHNICAL WHITE PAPER

## Table of Contents

VMware vSphere Hardening Guide Introduction .....	4
Scope .....	4
Recommendation Level .....	4
Testing for Configurations .....	5
Guideline Organization .....	5
Virtual Machine .....	5
VMware ESX/ESXi Host .....	5
vNetwork (Virtual Networking) .....	5
VMware vCenter .....	5
Console Operating System (COS) .....	5
Guideline Templates .....	6
Type A: Parameter Setting .....	6
Type B: Component Configuration .....	7
Type C: Operational Patterns .....	9
<b>Virtual Machines .....</b>	<b>10</b>
Unprivileged User Actions .....	10
Virtual Devices .....	11
Virtual Machine Information Flow .....	13
Virtual Machine Management APIs .....	16
VMware VMsafe .....	18
VMware VMsafe CPU/Memory API .....	18
VMware VMsafe Network API .....	19
General Virtual Machine Protection .....	21
<b>VMware ESX/ESXi Host .....</b>	<b>24</b>
Installation .....	24
Storage .....	24
Host Communications .....	26
Logging .....	29
Management .....	31
Host Console .....	36
<b>vNetwork (Virtual Networking) .....</b>	<b>41</b>
Network Architecture .....	41
vNetwork Configuration .....	46
Physical Network .....	52

VMware vCenter .....	54
VMware vCenter Server Host .....	54
VMware vCenter Server Communication .....	59
VMware vCenter Server Database .....	64
VMware vSphere Client Components .....	65
VMware vCenter Update Manager .....	66
Console Operating System (COS) .....	71
Console Network Protection .....	71
Console Management .....	72
Console Password Policies .....	75
Console Logging .....	78
Console Hardening .....	80
Console Access .....	82

# VMware vSphere Hardening Guide Introduction

## Scope

This set of documents provides guidance on how to securely deploy VMware vSphere™ 4.1 (“vSphere”) in a production environment. The focus is on *initial configuration of the virtualization infrastructure layer*, which covers the following:

- The virtualization hosts (both VMware® ESX® 4 and VMware ESXi™ 4).
- Configuration of the virtual machine container (**not** hardening of the guest operating system (OS) or any applications running within).
- Configuration of the virtual networking infrastructure, including the management and storage networks as well as the virtual switch (but **not** security of the virtual machine’s network).
- VMware vCenter™ Server, its database and client components.
- VMware vCenter Update Manager (Update Manager), included because the regular update and patching of the VMware ESX/ESXi hosts and the virtual machine containers are essential to maintaining the security of the environment.

The following are specifically out of scope and are **not** covered:

- Security of the software running inside the virtual machine, such as OS and applications, and the traffic traveling through the virtual machine networks.
- Security of any other add-on products, such as VMware vCenter Site Recovery Manager.
- Detailed operational procedures related to maintaining security, such as event monitoring, auditing and privilege management. Guidance is provided on general areas in which to perform these important tasks, but details on exactly how to perform them are out of scope.

## Recommendation Level

The recommendation level for a guideline consists of a rating that corresponds to the operational environment in which it is to be applied:

- **Enterprise:** This includes most enterprise production environments. The recommendations are meant to protect against most security attacks and provide protection of confidential information to the level required by all major security and compliance standards.
- **DMZ:** This includes environments that are particularly susceptible to targeted attacks. Examples include: Internet-facing hosts, internal systems with highly confidential or regulated data, systems subject to security standards such as the PCI-DSS, and so on.

*NOTE: Despite the name, this level should not be restricted to only DMZ hosts. Each organization should make its own determination as to the applicability of this level.*

- **Specialized Security Limited Functionality (SSLF):** This represents specialized environments that have some unique aspect that makes them especially vulnerable to sophisticated attacks. Recommendations at this level might result in loss of functionality or inability to use certain features. Careful consideration must be given to determining the applicability of these recommendations, including the possibility of using alternate compensating controls.

Unless otherwise specified, higher security levels include all recommendations from lower levels. For example, a DMZ environment should implement all level enterprise and DMZ recommendations, except when otherwise specified (e.g., a parameter that should be set to one value at level enterprise but a different value at level DMZ).

## Testing for Configurations

Most configuration parameters can be viewed using the vSphere Client as well as probed using an API client such as VMware vSphere 4 PowerCLI (PowerCLI) or vSphere Command-Line Interface (vCLI). These methods are all equivalent and nothing in this guide should be viewed as requiring a certain test method unless otherwise indicated.

## Guideline Organization

All recommendations are annotated using a code that consists of three letters followed by a two-digit number (starting with 01). The three-letter codes are as follows:

### Virtual Machine

- VMX: Virtual machine (vmx) parameters
- VMP: General virtual machine protection

### VMware ESX/ESXi Host

Unless otherwise specified, all guidelines apply to both VMware ESX 4 and ESXi 4.

- HIN: Installation
- HST: Storage
- HCM: Host communication
- HLG: Logging
- HMT: Management
- HCN: Host console

### vNetwork (Virtual Networking)

- NAR: Network architecture
- NCN: vNetwork configuration
- NPN: Physical network

### VMware vCenter

- VSH: VMware vCenter Server host
- VSC: VMware vCenter Server communication
- VSD: VMware vCenter Server database
- VCL: VMware vSphere Client components
- VUM: VMware vCenter Update Manager

### Console Operating System (COS)

*NOTE: These guidelines apply only to VMware ESX 4, not to VMware ESXi 4.*

- CON: Console OS networks
- COM: Console OS management
- COP: Console OS password policies
- COL: Console OS logging
- COH: Console OS hardening
- COA: Console OS access

## Guideline Templates

The following templates are used to define the guidelines.

Because a particular security issue might require different recommendations for different operating environments, it is possible that one guideline might have multiple recommendations. The following templates use shading to indicate which parts are common to all recommendations and which parts are unique.

### Type A: Parameter Setting

Use this template type when the recommendation specifies a configuration parameter to set (or not set) in specific products.

Examples:

- VMX parameters
- VMware ESX parameters
- VMware vCenter parameters
- COS parameters

PARAMETER ELEMENT	DESCRIPTION
Code	Code String
Name	Short name of guideline.
Description	Description of the interface or feature that the parameter governs.
Threat	Description of the specific threat exposed by this feature, including characterization of vulnerability.
Recommendation Level	<See recommendation-level descriptions>.
Parameter Setting	Where the parameter is defined, and what the recommended or not recommended values are. It's also indicated if there are preferred ways of setting the value (e.g., for a COS parameter, using the API instead of directly editing a configuration file).
Effect on Functionality	If this setting is adopted, what possible effects does it have on functionality? Does some feature stop working? Is there some information missing from a UI (and so on)?

Example:

PARAMETER ELEMENT	DESCRIPTION
Code	VMX01
Name	Prevent virtual disk shrinking.
Description	Shrinking a virtual disk reclaims unused space in it. If there is empty space in the disk, this process reduces the amount of space the virtual disk occupies on the host drive. Normal users and processes—that is, users and processes without root or administrator privileges—within virtual machines have the capability to invoke this procedure. However, if this is done repeatedly, the virtual disk can become unavailable while this shrinking is being performed, effectively causing a denial of service. In most datacenter environments, disk shrinking is not done, so you should disable this feature by setting the parameters listed in Table 9.

PARAMETER ELEMENT	DESCRIPTION
Threat	Repeated disk shrinking can make a virtual disk unavailable. Capability is available to nonadministrative users in the guest.
Recommendation Level	Enterprise.
Parameter Setting	isolation.tools.diskWiper.disable=TRUE isolation.tools.diskShrink.disable=TRUE
Effect on Functionality	

### Type B: Component Configuration

Use this template type when the guideline recommends a certain configuration of components, either to reduce risk or to provide a compensating control. Typically, these involve setting some parameter to a site-specific value or installing some components in a manner that satisfies some constraint, so there is no definitive value to be checked against.

Examples include:

- Configure an NTP server.
- Isolate management networks.
- Install Update Manager on a separate server.

CONFIGURATION ELEMENT	DESCRIPTION
Code	Code String
Name	Short name of guideline.
Description	Description of the component being addressed and the configuration being recommended.
Risk or Control	Description of the risk being mitigated, including characterization of vulnerability if applicable.
Recommendation Level	<See recommendation-level descriptions>.
Parameters or Objects Configuration	All the parameters or objects involved, and how they should be configured.
Test	Any procedure or way to show evidence that the guideline is being followed, if this is possible.

Example:

CONFIGURATION ELEMENT	DESCRIPTION	
Code	NAR02	
Name	Ensure that VMware vMotion™ (vMotion) traffic is isolated.	
Description	The security issue with vMotion migrations is that information is transmitted in plain text. Anyone with access to the network over which this information flows might view it. Ensure that vMotion traffic is separate from production traffic on an isolated network. This network should be a nonroutable (no layer-3 router spanning this and other networks), which will prevent any outside access to the network.	
Risk or Control	Attackers can sniff vMotion traffic to obtain memory content of a virtual machine. They might also potentially stage a man-in-the-middle (MiTM) attack in which the contents are modified during migration.	
Recommendation Level	Enterprise.	SSLF.
Parameters or Objects Configuration	The vMotion port group should be in a dedicated VLAN on a common virtual switch (vSwitch). The vSwitch can be shared with production (virtual machine) traffic, as long as the vMotion port group's VLAN is not used by production virtual machines.	The vMotion port group should be on a management-only vSwitch.
Effect on Functionality		At least one additional physical network adaptor must be dedicated to management (more if network adaptor teaming is used). This can greatly increase the cost of the physical networking infrastructure required; in resource-constrained environments (such as blades), this might not be possible to achieve.
Test	<ul style="list-style-type: none"> <li>• Check for usage of VLAN ID on non-vMotion port groups.</li> <li>• Check that VLAN is isolated and not routed in the physical network.</li> </ul>	In addition to enterprise tests: <ul style="list-style-type: none"> <li>• Check that the vMotion port group vSwitch does not contain any nonmanagement port groups.</li> <li>• Check that the physical network is not accessed by any other nonmanagement entity.</li> </ul>



### Type C: Operational Patterns

This type of template should be used to describe recommendations on how to operate or interact with the administrative components of the system.

Examples include:

- Use vSphere Client and VMware vCenter instead of COS.
- Avoid Linux-based clients unless on a secure network.
- Use certificates signed by an authority.

OPERATIONAL ELEMENT	DESCRIPTION
Code	Code String
Name	Short name of guideline.
Description	Description of the operational pattern or condition.
Risk or Control	Description of the risk being mitigated.
Recommendation Level	<See recommendation level descriptions>.
Condition or Steps	Concise description of the specific conditions to meet or avoid, and/or the steps needed to achieve this.
Test	Any procedure or way to show evidence that the guideline is being followed, if this is possible.

Here is an example:

CONFIGURATION ELEMENT	DESCRIPTION
Code	HCM01
Name	Do not use default self-signed certificates for VMware ESX/ESXi communication.
Description	Replace default self-signed certificates with those from a trusted certification authority (CA), either a commercial CA or an organizational CA.
Risk or Control	The use of default certificates leaves the SSL connection open to MiTM attacks. Changing the default certificates to trusted CA-signed certificates mitigates the potential for MiTM attacks.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	Information on how to replace default self-signed certificates can be found in both the <i>VMware ESXi Configuration Guide</i> and the <i>VMware ESX Configuration Guide</i> , “Security” chapter, “Authentication and User Management” sections, “Encryption and Security Certificates for VMware ESX/ESXi” subsection. This section covers the following advanced customization options: <ul style="list-style-type: none"> <li>• Configuring SSL timeouts</li> <li>• Configuration for certificates in nondefault locations</li> </ul> <p>The two guides can be found at these URLs:</p> <ul style="list-style-type: none"> <li>• <a href="http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esx_server_config.pdf">http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esx_server_config.pdf</a></li> <li>• <a href="http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esxi_server_config.pdf">http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esxi_server_config.pdf</a></li> </ul>
Test	Ensure that any certificates presented by the host can be verified by a trusted certification authority.

## Virtual Machines

Virtual machines are encapsulated in a small number of files. One of the important files is the configuration file (.vmx), which governs the behavior of the virtual hardware and other settings. You can see and modify the configuration settings by viewing the .vmx file directly in a text editor or by checking the settings in the vSphere Client, using the following procedure:

1. Choose the virtual machine in the inventory panel.
2. Click **Edit Settings**. Click **Options > Advanced/General**.
3. Click **Configuration Parameters** to open the configuration parameters dialog box.

You can also use any vSphere API-based tool such as PowerCLI to view and modify VMX parameters. In many instances, a VMX parameter has two versions: XXX.disable and XXX.enable. In nearly all cases, it is better to use the form XXX.disable=TRUE to disable a feature, because these are all parsed centrally in the VMX code.

Whether you change a virtual machine's settings in the vSphere Client, in a vSphere API-based tool or using a text editor, you must restart the virtual machine for most changes to take effect.

The following sections provide guidelines you should observe when dealing with these and other virtual machine files.

### Unprivileged User Actions

PARAMETER ELEMENT	DESCRIPTION
Code	VMX01
Name	Prevent virtual disk shrinking.
Description	Shrinking a virtual disk reclaims unused space in it. If there is empty space in the disk, this process reduces the amount of space the virtual disk occupies on the host drive. Normal users and processes—that is, users and processes without root or administrator privileges—within virtual machines have the capability to invoke this procedure. However, if this is done repeatedly, the virtual disk can become unavailable while this shrinking is being performed, effectively causing a denial of service. In most datacenter environments, disk shrinking is not done, so you should disable this feature by setting the parameters listed in Table 9.
Threat	Repeated disk shrinking can make a virtual disk unavailable. Capability is available to nonadministrative users in the guest.
Recommendation Level	Enterprise
Parameter Setting	isolation.tools.diskWiper.disable=TRUE isolation.tools.diskShrink.disable=TRUE
Effect on Functionality	

PARAMETER ELEMENT	DESCRIPTION
Code	VMX02
Name	Prevent other users from spying on administrator remote consoles.
Description	By default, remote console sessions can be connected to by more than one user at a time. When multiple sessions are activated, each terminal window gets a notification about the new session.
Threat	If an administrator in the virtual machine logs in using a VMware remote console during the session, a nonadministrator in the virtual machine might connect to the console and observe the administrator's actions. This might also result in an administrator's losing console access to a virtual machine. For example, if a jump box is being used for an open console session, and the administrator loses connection to that box, the console session remains open.
Recommendation Level	DMZ
Parameter Setting	RemoteDisplay.maxConnections=1
Effect on Functionality	Only one remote console connection to the virtual machine will be permitted. Other attempts will be rejected until the first session disconnects.

Copy-and-paste to and from the virtual machine console is disabled by default on vSphere 4.1. Please see this VMware knowledge base article for details: <http://kb.vmware.com/kb/1026437>.

## Virtual Devices

PARAMETER ELEMENT	DESCRIPTION
Code	VMX10
Name	Ensure that unauthorized devices are not connected.
Description	<p>Besides disabling unnecessary virtual devices from within the virtual machine, you should ensure that no device is connected to a virtual machine if it is not required to be there. For example, serial and parallel ports are rarely used for virtual machines in a datacenter environment, and CD/DVD drives are usually connected only temporarily during software installation.</p> <p>For less commonly used devices that are not required, either the parameter should not be present or its value must be FALSE.</p> <p><i>NOTE: The parameters listed are not sufficient to ensure that a device is usable; other parameters are required to indicate specifically how each device is instantiated.</i></p>
Threat	Any enabled or connected device represents another potential attack channel.
Recommendation Level	Enterprise.

PARAMETER ELEMENT	DESCRIPTION
Parameter Setting	The following parameters either should NOT be present or should be set to FALSE, unless the device is required: 1. Floppy drives: floppyX.present 2. Serial ports: serialX.present 3. Parallel ports: parallelX.present 4. USB controller: usb.present 5. CD-ROM: ideX:Y.present
Effect on Functionality	

PARAMETER ELEMENT	DESCRIPTION
Code	VMX11
Name	Prevent unauthorized removal, connection and modification of devices.
Description	Normal users and processes—that is, users and processes without root or administrator privileges—within virtual machines have the capability to connect or disconnect devices, such as network adaptors and CD-ROM drives, as well as the ability to modify device settings.  In general, you should use the virtual machine settings editor or configuration editor to remove any unneeded or unused hardware devices. However, you might want to use the device again, so removing it is not always a good solution. In that case, you can prevent a user or running process in the virtual machine from connecting or disconnecting a device from within the guest operating system, as well as modifying devices, by adding the following parameters.
Threat	By default, a rogue user with nonadministrator privileges in a virtual machine can: <ul style="list-style-type: none"> <li>• Connect a disconnected CD-ROM drive and access sensitive information on the media left in the drive</li> <li>• Disconnect a network adaptor to isolate the virtual machine from its network, which is a denial of service</li> <li>• Modify settings on a device</li> </ul>
Recommendation Level	Enterprise.
Parameter Setting	isolation.device.connectable.disable=TRUE isolation.device.edit.disable=TRUE
Effect on Functionality	

Virtual machine communications interface (VMCI) is a new type of interface designed to provide efficient and controlled communication between virtual machines and trusted endpoints on the host, such as the VMkernel, and from virtual machine to virtual machine.

The main objective of VMCI is to provide a socket-based framework for a new generation of applications that will exist only on virtual machines. More information on how to use this interface is detailed here: <http://www.vmware.com/support/developer/vmci-sdk>

This interface is implemented as a virtual PCI device, present by default in all virtual machines created with virtual hardware version 7, common in vSphere 4, VMware Fusion® and VMware Workstation 6 and above. A device driver is included and is installed by default with the VMware Tools software package in supported guest operating systems.

The interface currently has only two settings: enabled and restricted. In the enabled setting, a virtual machine can be detected and can potentially interact with all other virtual machines that also have the enabled setting. The default is restricted. The formal recommendation is to keep it restricted unless there is a reason to enable it—in this case, an application that is specifically created to leverage this feature.

PARAMETER ELEMENT	DESCRIPTION
Code	VMX12
Name	Disable virtual machine-to-virtual machine communication through VMCI.
Description	<p>If the interface is not restricted, a virtual machine can detect and be detected by all other virtual machines with the same option enabled within the same host. This might be the intended operation, but custom-built software can have unexpected vulnerabilities that might potentially lead to an exploit. Additionally, it is possible for a virtual machine to detect how many other virtual machines are within the same VMware ESX system by simply registering the virtual machine. This information might also be used for a potentially malicious objective.</p> <p>By default, the setting is FALSE.</p>
Threat	The virtual machine can be exposed to other virtual machines within the same system as long as there is at least one program connected to the VMCI socket interface.
Recommendation Level	Enterprise.
Parameter Setting	vmci0.unrestricted=FALSE
Effect on Functionality	

## Virtual Machine Information Flow

Virtual machines can write troubleshooting information to a virtual machine log file (vmware.log) stored on the VMware vStorage Virtual Machine File System (VMware vStorage VMFS) volume used to store other files for the virtual machine. Virtual machine users and processes can be configured to abuse the logging function, either intentionally or inadvertently, so that large amounts of data flood the log file. Over time, the log file can consume so much of the VMware ESX/ESXi host's file system space that it fills the hard disk, causing an effective denial of service, because the datastore can no longer accept new writes.

In addition to logging, guest operating system processes can send informational messages to the VMware ESX/ESXi host through VMware Tools. These messages, known as setinfo messages, are written to the virtual machine's configuration file (.vmx). They typically contain name-value pairs that define virtual machine characteristics or identifiers that the host stores—for example, ipaddress=10.17.87.224. A setinfo message has no predefined format and can be of any length. However, the total size of the VMX file is limited by default to 1MB.

PARAMETER ELEMENT	DESCRIPTION	
Code	VMX20	
Name	Limit virtual machine log file size and number.	
Description	<p>You can use these settings to limit the total size and number of log files. Normally a new log file is created only when a host is rebooted, so the file can grow to be quite large. You can ensure that new log files are created more frequently by limiting the maximum size of the log files. If you want to restrict the total size of logging data, VMware recommends saving 10 log files, each one limited to 1,000KB. Datastores are likely to be formatted with a block size of 2MB or 4MB, so a size limit too far below this size would result in unnecessary storage utilization.</p> <p>Each time an entry is written to the log, the size of the log is checked; if it is over the limit, the next entry is written to a new log. If the maximum number of log files already exists, when a new one is created, the oldest log file is deleted. A denial-of-service attack that avoids these limits might be attempted by writing an enormous log entry. But each log entry is limited to 4KB, so no log files are ever more than 4KB larger than the configured limit.</p> <p>A second option is to disable logging for the virtual machine. Disabling logging for a virtual machine makes troubleshooting challenging and support difficult. You should not consider disabling logging unless the log file rotation approach proves insufficient.</p>	
Threat	Uncontrolled logging can lead to denial of service due to the datastore's being filled.	
Recommendation Level	Enterprise.	SSLF.
Parameter Setting	log.rotateSize=1000000 log.keepOld=10	logging=FALSE
Effect on Functionality		Virtual machine logs unavailable for troubleshooting and support.

PARAMETER ELEMENT	DESCRIPTION	
Code	VMX21	
Name	Limit informational messages from the virtual machine to the VMX file.	
Description	<p>The configuration file containing these name-value pairs is limited to a size of 1MB. This 1MB capacity should be sufficient for most cases, but you can change this value if necessary. You might increase this value if large amounts of custom information are being stored in the configuration file. The default limit is 1MB. This limit is applied even when the size limit parameter is not listed in the .vmx file.</p>	
Threat	Uncontrolled size for the VMX file can lead to denial of service if the datastore is filled.	
Recommendation Level	Enterprise	
Parameter Setting	tools.setInfo.sizeLimit=1048576	
Effect on Functionality		

PARAMETER ELEMENT	DESCRIPTION
Code	VMX22
Name	Avoid using independent nonpersistent disks.
Description	<p>The security issue with nonpersistent disk mode is that successful attackers, with a simple shutdown or reboot, might undo or remove any traces that they were ever on the machine.</p> <p>To safeguard against this risk, you should set production virtual machines to use either persistent disk mode or nonpersistent disk mode; additionally, make sure that activity within the virtual machine is logged remotely on a separate server, such as a syslog server or equivalent Windows-based event collector.</p>
Threat	Without a persistent record of activity on a virtual machine, administrators might never know whether they have been attacked or hacked.
Recommendation Level	DMZ
Parameter Setting	<p>If remote logging of events and activity is not configured for the guest, scsiX:Y mode should be either:</p> <ol style="list-style-type: none"> <li>1. Not present</li> <li>2. Not set to independent nonpersistent</li> </ol>
Effect on Functionality	Won't be able to make use of nonpersistent mode, which allows rollback to a known state when rebooting the virtual machine.

A new feature in vSphere 4.1 is the ability to direct the serial port output of a virtual machine to a network destination, instead of just a local destination. This allows the use of "virtual serial port concentrators" to interact with multiple virtual machine serial ports from a single interface. Because serial port connections to virtual machines are low level, they might not have as strong controls over access or monitoring. Therefore, the access to virtual serial ports should be tightly controlled.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VMX23
Name	Use secure protocols for virtual serial port access.
Description	Serial ports are interfaces for connecting peripherals to the virtual machine. They are often used on physical systems to provide a direct, low-level connection to the console of a server. A virtual serial port allows for the same access to a virtual machine.
Risk or Control	Serial ports allow for low-level access, which often does not have strong controls such as logging or privileges.
Recommendation Level	Enterprise
Condition or Steps	Use a secure protocol such as telnets as opposed to telnet to access virtual serial ports.

PARAMETER ELEMENT	DESCRIPTION	
Code	VMX24	
Name	Disable certain unexposed features.	
Description	<p>Because VMware virtual machines are designed to work both on vSphere and on hosted virtualization platforms such as VMware Workstation and VMware Fusion, there are some VMX parameters that don't apply when running on vSphere. Although the functionality governed by these parameters is not exposed on VMware ESX, explicitly disabling them will reduce the potential for vulnerabilities.</p> <p><i>NOTE: Setting "isolation.tools.hgfsServerSet.disable = TRUE" disables the registration of the guest's HGFS server with the host. Without this, APIs that use HGFS to transfer files to/from the guest (such as some VIX commands or the VMware Tools auto-upgrader) won't work.</i></p>	
Threat	Disabling these features reduces the number of vectors through which a guest can attempt to influence the host, so it might help prevent successful exploits.	
Recommendation Level	DMZ	SSLF
Parameter Setting	isolation.tools.unity.push.update.disable = TRUE  isolation.tools.ghi.launchmenu.change = TRUE  isolation.tools.memSchedFakeSampleStats.disable = TRUE  isolation.tools.getCreds.disable = TRUE	isolation.tools.hgfsServerSet.disable = TRUE
Effect on Functionality	None.	APIs that use HGFS to transfer files to/from the guest (such as some VIX commands or the VMware Tools auto-upgrader) won't work.

## Virtual Machine Management APIs

The VIX API is high level and practical for both script writers and application programmers. It runs on either Windows or Linux and supports management of VMware Workstation, VMware Server and VMware vSphere, including VMware ESX/ESXi and vCenter Server. Additionally, bindings are provided for C, Perl and COM (Visual Basic, VBscript, C#).

PARAMETER ELEMENT	DESCRIPTION
Code	VMX30
Name	Disable remote operations within the guest.
Description	<p>The VIX API enables systems administrators to write programs and scripts that automate virtual machine operations as well as guest operating systems within the virtual machines themselves. If enabled, the system administrator can execute scripts or programs that use the VIX API to execute tasks within the guest OS.</p> <p>Add text here: For more information on this setting, please see the following KB article: <a href="http://kb.vmware.com/kb/1010103">http://kb.vmware.com/kb/1010103</a></p>



PARAMETER ELEMENT	DESCRIPTION
Threat	An adversary potentially can execute unauthorized scripts within the guest OS. Although this interface is governed by an SSL certificate, this certificate is not validated
Recommendation Level	SSLF
Parameter Setting	guest.command.enabled=FALSE
Effect on Functionality	This setting disables the operation of certain add-on products, such as VMware Consolidated Backup (VCB) and VMware Update Manager (VUM), both of which call the VIX API for guest operations.

vSphere 4.0 introduces the integration of virtual machine performance counters such as CPU and memory into PerfMon for Microsoft Windows guest operating systems when VMware Tools is installed. With this feature, virtual machine owners can do accurate performance analysis within the guest operating system.

The PerfMon integration in vSphere 4 leverages the guest SDK API to get to the accurate counters from the hypervisor. The programming guide for vSphere guest SDK 4.1 is available at <http://www.vmware.com/support/developer/guest-sdk/>. The list of available performance counters is on page 11 of the PDF (accessor functions for virtual machine data).

There is some information about the host that can optionally be exposed to the virtual machine guests:

- GUESTLIB\_HOST\_CPU\_NUM\_CORES
- GUESTLIB\_HOST\_CPU\_USED\_MS
- GUESTLIB\_HOST\_MEM\_SWAPPED\_MB
- GUESTLIB\_HOST\_MEM\_SHARED\_MB
- GUESTLIB\_HOST\_MEM\_USED\_MB
- GUESTLIB\_HOST\_MEM\_PHYS\_MB
- GUESTLIB\_HOST\_MEM\_PHYS\_FREE\_MB
- GUESTLIB\_HOST\_MEM\_KERN\_OVHD\_MB
- GUESTLIB\_HOST\_MEM\_MAPPED\_MB
- GUESTLIB\_HOST\_MEM\_UNMAPPED\_MB

The default is not to expose this information. Ordinarily you wouldn't want the guest to know anything about the host it is running on.

PARAMETER ELEMENT	DESCRIPTION
Code	VMX31
Name	Do not send host performance information to guests.
Description	If enabled, a virtual machine can obtain detailed information about the physical host. The default value for the parameter is FALSE. This setting should not be TRUE unless a particular virtual machine requires this information for performance monitoring.
Threat	An adversary potentially can use this information to inform further attacks on the host.
Recommendation Level	Enterprise.
Parameter Setting	tools.guestlib.enableHostInfo=FALSE
Effect on Functionality	

## VMware VMsafe

VMware VMsafe™ provides a security architecture for virtualized environments and an API-sharing program to enable partners to develop security products for virtualized environments. It consists of three parts:

- VMware VMsafe memory and CPU API (VMware VMsafe memory/CPU): Inspections of memory accesses and CPU states.
- VMware VMsafe network packet inspection API (VMware VMsafe Net): The VMware VMsafe Net enables you to create agents that inspect network packets at a point in the packet stream between the virtual network adaptor (vNIC) and a vSwitch that sits in front of a physical network adaptor (pnetwork adaptor). The interface provided is a function call library located in the same security appliance where the control path agent resides. The data path and control path agents communicate using the function calls from the library.
- VMware VMsafe Virtual Disk Development Kit (VDDK): The VDDK is separately published. Using the VDDK, you can create applications that manage virtual disk volumes. This enables you to inspect for and prevent malicious access and modification of data in protected disks.

The VDDK API is built into vSphere and cannot be disabled. Any entity wishing to make use of this API must present the proper credentials of an authorized user to vSphere. The method of controlling access to this API is to use the vSphere Roles and Permissions system. The user whose credentials are presented must have permission to access and modify the datastore on which the protected virtual machine's virtual disks reside.

*NOTE: This does not need to be a virtual machine running on the host; any application that has network access to a VMware ESX/ESXi host connected to the datastore can access the VDDK API.*

### VMware VMsafe CPU/Memory API

In order for a virtual machine to view and modify the CPU and memory contents of other virtual machines on the host, it must have access to the CPU/memory APIs. This access is enabled by attaching the virtual machine to a special VMware VMsafe introspection vSwitch.

Communication with hypervisor extension occurs over an isolated network created specifically for this purpose. A security appliance must be configured on this network before it can access the CPU and memory APIs.

By default, the CPU and memory of a virtual machine cannot be inspected or modified. To enable this functionality, the following settings must be present in the .vmx configuration file for each virtual machine that is to be protected:

- vmsafe.enable = TRUE
- vmsafe.agentAddress="www.xxx.yyy.zzz"
- vmsafe.agentPort="nnnn"

where "www.xxx.yyy.zzz" is the IP address and "nnnn" is the port number that the VMware VMsafe CPU/memory security virtual appliance uses to connect to the introspection virtual switch.

PARAMETER ELEMENT	DESCRIPTION
Code	VMX52
Name	Control access to virtual machines through VMware VMsafe CPU/memory APIs.
Description	A virtual machine must be configured explicitly to accept access by the VMware VMsafe CPU/memory API. This involves three parameters: one to enable the API; one to set the IP address used by the security virtual appliance on the introspection vSwitch; and one to set the port number for that IP address. This should be done only for virtual machines for which you want this to be done.

PARAMETER ELEMENT	DESCRIPTION
Threat	An attacker might compromise the virtual machine by making use of this introspection channel.
Recommendation Level	Enterprise.
Parameter Setting	<p>If a virtual machine is not supposed to be protected by a VMware VMsafe CPU/memory product, ensure that the following is not present in its VMX file:</p> <pre>vmsafe.enable=TRUE</pre> <pre>vmsafe.agentAddress="www.xxx.yyy.zzz"</pre> <pre>vmsafe.agentPort="nnnn"</pre> <p>The latter two parameters are based on how the VMware VMsafe security virtual appliance is configured; they should not be present at all if the virtual machine is not to be protected.</p>
Effect on Functionality	

### VMware VMsafe Network API

VMware VMsafe network API protection is enabled by a data path kernel module that must be installed on the VMware ESX/ESXi host by an administrator. This data path agent has the ability to inspect, modify and block network traffic going to and from a virtual machine's network adaptor ports. There can be up to 16 data path agents on one virtual machine network adaptor port. In addition, there typically would be a control path virtual appliance running on the host. This security virtual appliance must be attached to a special VMware VMsafe introspection vSwitch to communicate with the data path agent.

Communication with the data path kernel module occurs over an isolated network created specifically for this purpose. A security appliance must be configured on this network before it can access the data path kernel module.

In order for the security appliance to have access to the network packets of other virtual machines, the VMkernel must be configured to send information to it. This is done by setting a kernel parameter value to the IP address that the security virtual machine is using on the introspection virtual switch:

- /Net/DVFilterBindIpAddress

By default, the network traffic of a virtual machine cannot be inspected or modified. To enable this functionality, the following setting must be present in the .vmx configuration file for each virtual machine that is to be protected:

- ethernet0.filter1.name = dv-filter1

where "ethernet0" is the network adaptor interface of the virtual machine that is to be protected, "filter1" is the number of the filter that is being used, and "dv-filter1" is the name of the particular data path kernel module that is protecting the virtual machine. There can be up to 10 network adaptors per virtual machine (ethernet0 through ethernet9) and up to 16 filters per vNIC (filter0 through filter15).

PARAMETER ELEMENT	DESCRIPTION
Code	VMX55
Name	Control access to virtual machines through VMware VMsafe network APIs.
Description	A virtual machine must be configured explicitly to accept access by the VMware VMsafe network API. This should be done only for virtual machines for which you want this to be done.
Threat	An attacker might compromise the virtual machine by making use of this introspection channel.
Recommendation Level	Enterprise.
Parameter Setting	<p>If a virtual machine is not supposed to be protected by a VMware VMsafe CPU/memory product, ensure that the following is <b>not</b> present in its VMX file:</p> <pre>ethernet0.filter1.name = dv-filter1</pre> <p>where "ethernet0" is the network adaptor interface of the virtual machine that is to be protected, "filter1" is the number of the filter that is being used, and "dv-filter1" is the name of the particular data path kernel module that is protecting the virtual machine. If the virtual machine is supposed to be protected, ensure that the name of the data path kernel is set correctly.</p>
Effect on Functionality	

PARAMETER ELEMENT	DESCRIPTION
Code	VMX56
Name	Restrict access to VMware VMsafe network APIs.
Description	You should ensure that the only virtual machines configured on the VMware VMsafe network introspection vSwitch are those that you have specifically installed to perform this task.
Threat	An attacker might compromise all other virtual machines by making use of this introspection channel.
Recommendation Level	Enterprise.
Parameter Setting	<p>If a VMware VMsafe network security appliance has been deployed on a host, then ensure that this (and only this) virtual machine's IP address is configured to use this API. This should be done by ensuring that only this virtual machine's IP address appears in the following kernel parameter:</p> <ul style="list-style-type: none"> <li>• /Net/DVFilterBindIpAddress</li> </ul> <p>This can be done using the vCLI, for example, by issuing the command <code>vicfg-advcfg -g /Net/DVFilterBindIpAddress</code></p>
Effect on Functionality	

## General Virtual Machine Protection

OPERATIONAL ELEMENT	DESCRIPTION
Code	VMP01
Name	Secure virtual machines as you would secure physical machines.
Description	A key to understanding the security requirements of a virtualized environment is the recognition that a virtual machine is, in most respects, the equivalent of a physical server. Therefore, it is critical that you employ the same security measures in virtual machines that you would for physical servers.
Risk or Control	The guest operating system that runs in the virtual machine is subject to the same security risks as a physical system.
Recommendation Level	Enterprise.
Condition or Steps	Ensure that antivirus, antispysware, intrusion detection and other protection are enabled for every virtual machine in your virtual infrastructure. Make sure to keep all security measures up to date, including applying appropriate patches. It is especially important to keep track of updates for dormant virtual machines that are powered off, because it can be easy to overlook them.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VMP02
Name	Disable unnecessary or superfluous functions inside virtual machines.
Description	By disabling unnecessary system components that are not needed to support the application or service running on the system, you reduce the number of parts that can be attacked. Virtual machines often don't require as many services or functions as ordinary physical servers; so when virtualizing, you should evaluate whether a particular service or function is truly needed.
Risk or Control	Any service running in a virtual machine provides a potential avenue of attack.
Recommendation Level	Enterprise.
Condition or Steps	Some of these steps include: <ul style="list-style-type: none"> <li>• Disable unused services in the operating system. For example, if the system runs a file server, make sure to turn off any Web services.</li> <li>• Disconnect unused physical devices, such as CD/DVD drives, floppy drives and USB adaptors. This is described in the "Removing Unnecessary Hardware Devices" section in the <i>VMware ESX Configuration Guide</i>.</li> <li>• Turn off any screen savers. If using a Linux, BSD or Solaris guest operating system, do not run the X Window system unless it is necessary.</li> </ul>

OPERATIONAL ELEMENT	DESCRIPTION
Code	VMP03
Name	Use templates to deploy virtual machines whenever possible.
Description	By capturing a hardened base operating system image (with no applications installed) in a template, you can ensure that all your virtual machines are created with a known baseline level of security. You can then use this template to create other, application-specific, templates or use the application template to deploy virtual machines.
Risk or Control	Manual installation of the OS and applications into a virtual machine introduces the risk of misconfiguration due to human or process error.
Recommendation Level	Enterprise.
Condition or Steps	Provide templates for virtual machine creation that contain hardened, patched and properly configured OS deployments. If possible, predeploy applications in templates as well, although care should be taken that the application doesn't depend upon virtual machine-specific information to be deployed. In vSphere, you can convert a template to a virtual machine and back again quickly, which makes updating templates quite easy. VMware Update Manager also provides the ability to automatically patch the operating system and certain applications in a template, thereby ensuring that they remain up to date.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VMP04
Name	Prevent virtual machines from taking over resources.
Description	By default, all virtual machines on a VMware ESX/ESXi host share the resources equally. By using the resource management capabilities of VMware ESX/ESXi, such as shares and limits, you can control the server resources that a virtual machine consumes.
Risk or Control	You can use this mechanism to prevent a denial of service that causes one virtual machine to consume so much of the host's resources that other virtual machines on the same host cannot perform their intended functions.
Recommendation Level	DMZ.
Condition or Steps	Use shares or reservations to guarantee resources to critical virtual machines. Use limits to constrain resource consumption by virtual machines that have a greater risk of being exploited or attacked, or ones that run applications that are known to have the potential to greatly consume resources.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VMP05
Name	Minimize use of the virtual machine console.
Description	The virtual machine console enables you to connect to the console of a virtual machine, in effect seeing what a monitor on a physical server would show.
Risk or Control	The virtual machine console also provides power management and removable device connectivity controls, which might potentially allow a malicious user to bring down a virtual machine. In addition, it also has a performance impact on the service console, especially if many virtual machine console sessions are open simultaneously.
Recommendation Level	Enterprise.
Condition or Steps	Instead of virtual machine console, use native remote management services, such as terminal services and SSH, to interact with virtual machines. Grant virtual machine console access only when necessary.

## VMware ESX/ESXi Host

### Installation

OPERATIONAL ELEMENT	DESCRIPTION
Code	HIN01
Name	Verify integrity of software before installation.
Description	Before installing any software from VMware, its authenticity and integrity should be verified. VMware provides digital signatures for downloaded software, and physical seals for software distributed via physical media.
Risk or Control	Software tampering can be used to break security.
Recommendation Level	Enterprise.
Condition or Steps	Always check the SHA1 hash after downloading an ISO from download.vmware.com to ensure the ISO image's authenticity. If you obtain media from VMware and the security seal is broken, return the software to VMware for a replacement.

OPERATIONAL ELEMENT	DESCRIPTION
Code	HIN02
Name	Keep VMware ESX/ESXi system properly patched.
Description	By staying up to date on VMware ESX/ESXi patches, vulnerabilities in the hypervisor can be mitigated.
Risk or Control	If an attacker can obtain access and elevate privileges on the VMware ESX/ESXi system, they can then take over the virtual machines on that host.
Recommendation Level	Enterprise.
Condition or Steps	Employ a system to keep the VMware ESX/ESXi system up to date with patches in accordance with industry-standard guidelines, or internal guidelines where appropriate. VMware vCenter Update Manager is an automated tool that can greatly assist with this. VMware also publishes advisories on security patches, and offers a way to subscribe to email alerts for them.

### Storage

PARAMETER ELEMENT	DESCRIPTION
Code	HST01
Name	Ensure that bidirectional CHAP authentication is enabled for iSCSI traffic.
Description	vSphere allows for the use of bidirectional authentication of both the iSCSI target and host. Choosing not to enforce more stringent authentication can make sense if you create a dedicated network or VLAN to service all your iSCSI devices. If the iSCSI facility is isolated from general network traffic, it is less vulnerable to exploitation.



PARAMETER ELEMENT	DESCRIPTION
Threat	By not authenticating both the iSCSI target and host, there is a potential for a MiTM attack in which an attacker might impersonate either side of the connection to steal data. Bidirectional authentication can mitigate this risk.
Recommendation Level	DMZ.
Parameter Setting	Configuration → Storage Adaptors → iSCSI Initiator Properties → CHAP → CHAP (Target Authenticates Host) and Mutual CHAP (Host Authenticates Target), both set to "Use CHAP" and each with a "Name" and "Secret" configured.
Effect on Functionality	

OPERATIONAL ELEMENT	DESCRIPTION	
Code	HST02	
Name	Ensure uniqueness of CHAP authentication secrets.	
Description	The mutual authentication secret for each host should be different; if possible, the secret should be different for each client authenticating to the server as well. This ensures that if a single host is compromised, an attacker cannot create another arbitrary host and authenticate to the storage device.	
Risk or Control	With a single shared secret, compromise of one host can allow an attacker to authenticate to the storage device.	
Recommendation Level	DMZ.	SSLF.
Condition or Steps	Configure a different authentication secret for each VMware ESX/ESXi host.	Configure a different secret for each client authenticating to the server.

Zoning provides access control in a SAN topology. It defines which host bus adaptors (HBAs) can connect to which SAN device service processors. When a SAN is configured using zoning, the devices outside a zone are not detectable to the devices inside the zone. In addition, SAN traffic within each zone is isolated from the other zones. Within a complex SAN environment, SAN switches provide zoning, which defines and configures the necessary security and access rights for the entire SAN.

LUN masking is commonly used for permission management. It is also referred to as selective storage presentation, access control and partitioning, depending on the vendor. It is performed at the storage processor or server level. It makes a LUN invisible when a target is scanned. The administrator configures the disk array so each server or group of servers can detect only certain LUNs. Masking capabilities for each disk array are vendor specific, as are the tools for managing LUN masking.

OPERATIONAL ELEMENT	DESCRIPTION
Code	HST03
Name	Mask and zone SAN resources appropriately.
Description	You should use zoning and LUN masking to segregate SAN activity. For example, you manage zones defined for testing independently within the SAN so they do not interfere with activity in the production zones. Similarly, you can set up different zones for different departments. Zoning must take into account any host groups that have been set up on the SAN device.

OPERATIONAL ELEMENT	DESCRIPTION
Risk or Control	
Recommendation Level	Enterprise.
Condition or Steps	Zoning and masking capabilities for each SAN switch and disk array are vendor specific, as are the tools for managing LUN masking.

## Host Communications

To ensure the protection of the data transmitted to and from external network connections, VMware ESX uses the 256-bit AES block encryption. VMware ESX Server also uses 1,024-bit RSA for key exchange. Client sessions with the VMware ESX/ESXi host can be initiated from any vSphere API client, such as vSphere Client, VMware vCenter Server and the vCLI.

SSL encryption protects the connection to VMware ESX/ESXi, but the default certificates are not signed by a trusted certificate authority and do not provide the authentication security you might need in a production environment. These self-signed certificates are vulnerable to MiTM attacks, and clients receive a warning about them. If you intend to use encrypted remote connections externally, consider purchasing a certificate from a trusted certification authority or use your own security certificate for your SSL connections.

CONFIGURATION ELEMENT	DESCRIPTION
Code	HCM01
Name	Do not use default self-signed certificates for VMware ESX/ESXi communication.
Description	Replace default self-signed certificates with those from a trusted CA, either commercial or organizational.
Risk or Control	The use of default certificates leaves the SSL connection open to MiTM attacks. Changing the default certificates to trusted CA-signed certificates mitigates the potential for MiTM attacks.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>Information on how to replace default self-signed certificates can be found in both the VMware ESXi Configuration Guide and the VMware ESX Configuration Guide, "Security" chapter, "Authentication and User Management" section, "Encryption and Security Certificates for VMware ESX/ESXi" subsection. This section covers the following advanced customization options:</p> <ul style="list-style-type: none"> <li>• Configuring SSL timeouts</li> <li>• Configuration for certificates in nondefault locations</li> </ul> <p>The two guides can be found at these URLs:</p> <ul style="list-style-type: none"> <li>• <a href="http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esxi_server_config.pdf">http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esxi_server_config.pdf</a></li> <li>• <a href="http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esx_server_config.pdf">http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esx_server_config.pdf</a></li> </ul> <p>Additional information can be found in this document:</p> <ul style="list-style-type: none"> <li>• <a href="http://www.vmware.com/resources/techresources/10124">http://www.vmware.com/resources/techresources/10124</a></li> </ul>
Test	Ensure that any certificates presented by the host can be verified by a trusted certification authority.

The host agent (hostd) acts as a proxy for several services running on the VMware ESX/ESXi host. Most of the services are required for proper functioning of VMware ESX/ESXi, but there are some that can be disabled. This will limit some management and diagnostic functionality on the host.

The list of currently running services can be viewed as follows:

- On VMware ESXi: log into Tech Support Mode and issue the following command:

```
vim-cmd proxysvc/service_list
```

- On VMware ESX: log into the Service Console and issue the following command:

```
vmware-vim-cmd proxysvc/service_list
```

Services can be modified by following the instructions in the following VMware knowledge base article: <http://kb.vmware.com/kb/1016039>.

**NOTE:** The article is written for VMware ESX, but the information still applies for VMware ESXi with the following changes:

The command to use is “vim-cmd” instead of “vmware-vim-cmd.”

This command is executed in Tech Support Mode. The command to reenab the welcome Web page is

```
vim-cmd proxysvc/add_tcp_service "/" httpsWithRedirect localhost 8309
```

Changes take effect immediately and persist across reboots.

PARAMETER ELEMENT	DESCRIPTION
Code	HCM02
Name	Disable managed object browser.
Description	The managed object browser provides a way to explore the object model used by the VMkernel to manage the host; it enables configurations to be changed as well. This interface is used primarily for debugging the VMware vSphere 4 Web Services SDK.
Threat	This interface might potentially be used to perform malicious configuration changes or actions.
Recommendation Level	SSLF.
Parameter Setting	Instructions for how to disable the managed object browser can be found in VMware knowledge base article 1016039.
Effect on Functionality	The managed object browser will no longer be available for diagnostics.

PARAMETER ELEMENT	DESCRIPTION
Code	HCM03
Name	Disable vSphere Web Access (VMware ESX <b>only</b> ).
Description	<p>vSphere Web Access provides a means for users to view virtual machines on a single VMware ESX host and perform simple operations such as power-on and suspend. It also provides a way to obtain console access to virtual machines. All of this is governed by the user permissions on the local VMware ESX host.</p> <p>In most cases, users should manage virtual machines through VMware vCenter Server, using either the vSphere Client or the VMware vCenter vSphere Web Access.</p> <p><i>NOTE: VMware ESXi does not have vSphere Web Access. This guideline is not relevant for VMware ESXi.</i></p>
Threat	This is a Web interface and therefore has some of the general risks associated with all Web interfaces.
Recommendation Level	DMZ.
Parameter Setting	In the vSphere Client, select the host, click the <b>configuration tab</b> , and select the <b>Security Profile</b> item. Click <b>Properties</b> ; then in the list of services, ensure that the box for <b>vSphere Web Access</b> is unchecked.
Effect on Functionality	vSphere Web Access will no longer be available.

PARAMETER ELEMENT	DESCRIPTION
Code	HCM05
Name	Disable "Welcome" Web page.
Description	If you point a Web browser at the management interface of VMware ESX/ESXi, a static page is presented that contains links to the managed object browser, the host datastore browser and various downloads. Although the presence of this page doesn't actually change the security profile of the host, it might be desirable to not have it displayed at all.
Threat	This page might reveal information about the identity of a host to an attacker.
Recommendation Level	DMZ.
Parameter Setting	Instructions on how to disable the "Welcome" Web page can be found in VMware knowledge base article 1016039, with variations for VMware ESXi as noted above.
Effect on Functionality	The "Welcome" Web page will no longer be accessible.

Network file copy (NFC) is the name of the mechanism used to migrate or clone a virtual machine between two VMware ESX hosts over the network. The initial authentication for this transfer occurs using SSL. But by default, the actual data transfer occurs in plain text, for performance reasons.

Because this file transfer occurs over the management network, which itself should be isolated from all other nonmanagement traffic, the risk of data being leaked is related to the isolation of that management network.

If desired, SSL can be enabled on the data transfer part of NFC. If SSL is enabled, the NFC traffic will go through an SSL connection rather than a plain TCP connection. You can add the following entry in vpxd.cfg to enable NFC SSL.

```
<config>
  <nfc>
    <useSSL>true</useSSL>
  </nfc>
</config>
```

*NOTE: The use of SSL for NFC data transfer has not been extensively tested.*

PARAMETER ELEMENT	DESCRIPTION
Code	HCM06
Name	Use SSL for network file copy (NFC).
Description	NFC is the name of the mechanism used to migrate or clone a virtual machine between two VMware ESX hosts over the network. By default, SSL is used only for the authentication of the transfer. But if desired, SSL can also be enabled on the data transfer. Note that even if SSL is enabled for NFC, the certificate is not validated. So this can prevent sniffing, but will not prevent Man-in-the-middle attacks.
Threat	Virtual machine contents might be sniffed if the management network is not adequately isolated and secured.
Recommendation Level	SSLF.
Parameter Setting	Add the following entry in vpxd.cfg to enable NFC SSL.  <pre>&lt;config&gt;   &lt;nfc&gt;     &lt;useSSL&gt;true&lt;/useSSL&gt;   &lt;/nfc&gt; &lt;/config&gt;</pre>
Effect on Functionality	This setting likely will reduce performance of actions involving NFC, such as virtual machine clone or migration. In addition, it has not been extensively tested and might cause operations to fail in certain circumstances.

## Logging

The following sets of recommendations do not pertain to VMware ESX 4.1 (i.e., the “classic” VMware ESX architecture, with the console OS). They apply only to the VMware ESXi architecture. Logging for the VMware ESX architecture is covered separately in the “Console Operating System” section of this guide.

VMware ESXi 4.1 maintains a log of activity in log files, using a syslog facility.

The following logs are available:

- hostd.log
- messages
- vpxa.log (only if the host has been joined to a VMware vCenter Server instance)

There are several ways to view the contents of these log files.

To view the logs in a VMware vSphere Virtual Infrastructure Client (vSphere VI Client), take the following steps:

1. Log in directly to the VMware ESXi host using VI Client; make sure the host is selected in the inventory.
2. Click **Administration**; then click the **System Logs** tab.
3. Choose the log file you want to view in the drop-down menu in the upper left.

To view the logs in a Web browser, enter the URL `https://<hostname>/host`, where `<hostname>` is the host name or IP address of the management interface of the VMware ESXi host; then choose from the list of files presented. You can also use the vCLI command `vifs` to download the log files to your local system.

An important point to consider is that the log messages are not encrypted when sent to the remote host. So it is important that the network for the service console be strictly isolated from other networks.

Another point is that, by default, the logs on VMware ESXi are stored only in the in-memory file system. Only one day's worth of logs is stored, and it is lost upon reboot. Persistent logging to a datastore can be configured. It is recommended that this be done so that a dedicated record of server activity is available for that host.

CONFIGURATION ELEMENT	DESCRIPTION
Code	HLG01
Name	Configure remote syslog.
Description	Remote logging to a central host provides a way to greatly increase administration capabilities. By gathering log files onto a central host, you can easily monitor all hosts with a single tool. You can also do aggregate analysis and searching to look for such things as coordinated attacks on multiple hosts.
Risk or Control	Logging to a secure, centralized log server can help prevent log tampering; it also provides a long-term audit record.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	Remote syslog can be configured on a VMware ESXi host, using a remote command line, such as vCLI or PowerCLI, or an API client.
Test	Query the syslog configuration to make sure that a valid syslog server has been configured, including the correct port.

CONFIGURATION ELEMENT	DESCRIPTION
Code	HLG02
Name	Configure persistent logging.
Description	By default, the logs on VMware ESXi are stored only in the in-memory file system. Only one day's worth of logs is stored, and it is lost upon reboot. Persistent logging to a datastore can be configured. It is recommended that this be done so that a dedicated record of server activity is available for that host.
Risk or Control	In addition to remote syslog, having the log files for a server sent to a datastore provides a dedicated set of log records for that server, making it easier to monitor events and diagnose issues for that specific server.
Recommendation Level	Enterprise.

CONFIGURATION ELEMENT	DESCRIPTION
Parameters or Objects Configuration	Persistent logging to a datastore for a VMware ESXi host can be configured using the vSphere Client, vCLI or other API client. More information on how this can be done can be found in <i>vSphere Basic System Administration</i> in the “Configuring Hosts and vCenter Server” chapter, “System Log Files” section, “Configure Syslog on VMware ESXi Hosts” subsection.
Test	View the contents of the configured log file on the datastore to make sure that it is being updated with log messages.

CONFIGURATION ELEMENT	DESCRIPTION
Code	HLG03
Name	Configure NTP time synchronization.
Description	By ensuring that all systems use the same relative time source (including the relevant localization offset) and that the relative time source can be correlated to an agreed-upon time standard (such as Coordinated Universal Time—UTC), you can make it simpler to track and correlate an intruder’s actions when reviewing the relevant log files.
Risk or Control	Incorrect time settings can make it difficult to inspect and correlate log files to detect attacks and can make auditing inaccurate.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	NTP can be configured on a VMware ESXi host using the vSphere Client or a remote command line such as vCLI or PowerCLI. To avoid potential vulnerabilities in the NTP software, it is recommended to synchronize the VMware ESXi clock with a time server that is located on the management network rather than directly with a time server on a public network. This time server can then synchronize with a public source through a strictly controlled network connection with a firewall.
Test	<ul style="list-style-type: none"> <li>• Query the NTP configuration to make sure that a valid time source has been configured.</li> <li>• Make sure that the NTP service is running on the host.</li> </ul>

## Management

The Common Information Model (CIM) is an open standard that defines a framework for agentless, standards-based monitoring of hardware resources for VMware ESXi. This framework consists of a CIM object manager, often called a CIM broker, and a set of CIM providers.

CIM providers are used as the mechanism to provide management access to device drivers and underlying hardware. Hardware vendors, including server manufacturers and specific hardware device vendors, can write providers to provide monitoring and management of their particular devices. VMware also writes providers that implement monitoring of server hardware, VMware ESXi storage infrastructure and virtualization-specific resources. These providers run inside the VMware ESXi system and therefore are designed to be extremely lightweight and focused on specific management tasks. The CIM broker takes information from all CIM providers, and presents it to the outside world via standard APIs, the most common one being WS-MAN.

PARAMETER ELEMENT	DESCRIPTION
Code	HMT01
Name	Control access by CIM-based hardware monitoring tools.
Description	The CIM system provides an interface that enables hardware-level management from remote applications via a set of standard APIs. To ensure that the CIM interface is secure, provide only the minimum access necessary to these applications. Do not provision them with the root account or any other full administrator account; instead, provide an account that has only limited privileges.
Threat	If an application has been provisioned with a root or full administrator account, compromise of that application can lead to full compromise of the virtual environment.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>Do not provide root credentials to remote applications to access the CIM interface. Instead, create a service account specific to these applications. Read-only access to CIM information is granted to any local account defined on the VMware ESX/ESXi system, as well as any role defined in VMware vCenter Server.</p> <p>If the application requires write access to the CIM interface, only two privileges are required. It is recommended that you create a role to apply to the service account with only these privileges:</p> <ul style="list-style-type: none"> <li>• Host &gt; Config &gt; SystemManagement</li> <li>• Host &gt; CIM &gt; CIMInteraction</li> </ul> <p>This role can be either local to the host or centrally defined on VMware vCenter Server, depending on how the particular monitoring applications work.</p>
Test	Logging in to the host with the service account (e.g., using the VMware vSphere Client) should provide only read-only access, or only the two privileges previously indicated.

VMware ESXi 4.1 contains a different SNMP agent from that in VMware ESX 4.1, and it supports only versions 1 and 2c. It provides the same notifications as VMware ESX 4.1 and adds notifications for hardware-related sensors. Unlike VMware ESX 4.1, it supports only the SNMPv2-MIB, and only for discovery, inventory and diagnostics of the SNMP agent.

SNMP messages contain a field called the *community string*, which conveys context and usually identifies the sending system for notifications. This field also provides context for the instance of a MIB module on which the host should return information. VMware ESX/ESXi SNMP agents allow multiple community strings per notification target as well as for polling. Keep in mind that community strings are not meant to function as passwords but only as a method for logical separation.

CONFIGURATION ELEMENT	DESCRIPTION
Code	HMT02
Name	Ensure proper SNMP configuration (VMware ESXi <b>only</b> ).
Description	If SNMP is not being used, it should remain disabled. If it is being used, the proper trap destination should be configured.



CONFIGURATION ELEMENT	DESCRIPTION
Risk or Control	If SNMP is not properly configured, monitoring information can be sent to a malicious host that can then use this information to plan an attack.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	SNMP can be configured on a VMware ESXi host, using a remote command line, such as vCLI or PowerCLI, or an API client.
Test	If SNMP is not being used, make sure that it is not running.  If SNMP is being used, make sure the parameter settings have the right destination properly configured.

As with VMware ESX, VMware ESXi maintains its configuration state in a set of configuration files. However, on VMware ESXi these files can be accessed using only the remote file access API, and there are far fewer files involved. These files normally are not modified directly. Instead, their contents normally change indirectly because of some action invoked on the host. However, the file access API does allow for direct modification of these files, and some modifications might be warranted in special circumstances.

The following is a list of configuration-related files exposed via the vSphere API on VMware ESXi:

- esx.conf
- hostAgentConfig.xml
- hosts
- license.cfg
- motd
- openwsman.conf
- proxy.xml
- snmp.xml
- ssl\_cert
- ssl\_key
- syslog.conf
- vmware\_config
- vmware\_configrules
- vmware.lic
- vpxa.cfg

*NOTE: For the most up-to-date list, a live system with the latest patch release of VMware ESXi should be queried. The accessible and relevant configuration files are found by browsing to <https://<hostname>/host>.*

OPERATIONAL ELEMENT	DESCRIPTION
Code	HMT03
Name	Establish and maintain configuration file integrity (VMware ESXi <b>only</b> ).
Description	VMware ESXi maintains its configuration state in a set of configuration files. You should monitor all of these files for integrity and unauthorized tampering, either by periodically downloading them and tracking their contents or by using a commercial tool designed to do this. Any changes should be correlated with some approved administrative action, such as a configuration change.
Risk or Control	Tampering with these files has the potential to enable unauthorized access to the host configuration and virtual machines.
Recommendation Level	DMZ.
Condition or Steps	<p>The accessible and relevant configuration files in VMware ESXi 4.1 are found by browsing to <a href="https://&lt;hostname&gt;/host">https://&lt;hostname&gt;/host</a>.</p> <p>The files can be viewed or retrieved using this Web interface or with an API client (e.g., vCLI, PowerCLI). This provides a means to keep track of the files and their contents, to ensure that they are not improperly modified.</p> <p>Be sure not to monitor log files and other files whose content is expected to change regularly due to system activity. Also, account for configuration file changes that are due to deliberate administrative activity.</p> <p><i>NOTE: For file integrity monitoring on VMware ESX 4.1, refer to the section on the console operating system.</i></p>

VMware VMsafe provides a security architecture for virtualized environments and an API-sharing program to enable partners to develop security products for virtualized environments. For more information on VMware VMsafe, see the “Virtual Machine” section of this guide.

VMware VMsafe network API protection is enabled by a *data path* kernel module that must be installed on the VMware ESX/ESXi host by an administrator. This data path agent has the ability to inspect, modify and block network traffic going to and from a virtual machine’s network adaptor ports. In addition, there typically would be a *control path* virtual appliance running on the host. This security virtual appliance must be configured to communicate with the data path agent. This is done by setting a kernel parameter value to the IP address that the security virtual machine is using on the introspection virtual switch:

- /Net/DVFilterBindIpAddress

CONFIGURATION ELEMENT	DESCRIPTION
Code	HMT12
Name	Prevent unintended use of VMware VMsafe network APIs.
Description	If you are not using any products that make use of the VMware VMsafe network API, the host should not be configured to send network information to any virtual machine.
Risk or Control	If the API is enabled, an attacker might attempt to connect a virtual machine to it, thereby potentially providing access to the network of other virtual machines on the host.

CONFIGURATION ELEMENT	DESCRIPTION
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>If a VMware VMsafe network security appliance is not being used on the host, ensure that the following kernel parameter has a blank value:</p> <ul style="list-style-type: none"> <li>• /Net/DVFilterBindIpAddress</li> </ul> <p>This can be done using the vCLI, for example, by issuing the following command: vicfg-advcfg -g /Net/DVFilterBindIpAddress</p>

CONFIGURATION ELEMENT	DESCRIPTION
Code	HMT15
Name	Audit for the loading of unauthorized kernel modules (VMware ESXi <b>only</b> ).
Description	VMware provides digital signatures for third-party kernel modules that meet certain requirements. By default, the VMware ESXi host does not permit the loading of kernel modules that lack a valid digital signature. This can be overridden; however, a warning is sent to the system logs alerting the administrator anytime an unauthorized module is loaded.
Risk or Control	Malicious kernel modules can be used to take full control of the VMware ESXi host.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>The "messages" kernel log file will show an entry anytime an unsigned module is loaded into memory. This log file should be monitored and scanned for this text. The message will be of the following form:</p> <p>ALERT: Elf: NNNN: Kernel module XXXXX was loaded but has no signature attached.</p> <p>Where "NNNN" is a number and "XXXXX" is the name of the module.</p>

In order to control a VMware ESX/ESXi host, VMware vCenter Server creates a special user account called "vpxuser" on each host as it is joined to the inventory. This is a privileged account that acts as a proxy for all actions initiated through VMware vCenter Server. It is created and managed automatically on an ongoing basis. The vpxuser password is 32 characters long and is guaranteed to contain at least one symbol from the following four character classes:

1. Symbols in the set "-./:=[\]\^\_{}~"
2. Digits 0-9
3. Uppercase letters
4. Lowercase letters

The vpxuser password is randomly generated with the use of OpenSSL crypto libraries as a source of randomness. The expiration time is 30 days by default and can be changed in the VMware vCenter Server advanced options for VirtualCenter.VimPasswordExpirationInDays. The password length is 32 by default, but it can be changed by modifying vpxd.hostPasswordLength in the vpxd.cfg file.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	HMT20
Name	Ensure that vpxuser auto-password change meets policy.
Description	By default, the vpxuser password automatically will be changed by VMware vCenter Server every 30 days. Ensure that this setting meets your policies. If not, configure to meet password aging policies. <b>NOTE: It is very important that the password aging policy not be shorter than the interval that is set to automatically change the vpxuser password, to preclude the possibility that VMware vCenter Server might get locked out of a VMware ESX host.</b>
Risk or Control	If an attacker obtains the vpxuser password, the password can be used only for a limited amount of time.
Recommendation Level	DMZ.
Parameters or Objects Configuration	Configure the following parameter in the VMware vCenter Server advanced settings in the vSphere Client: vCenterVirtualCenterVimPasswordExpirationInDays  On a VMware ESX host, ensure that the value is set lower than the password aging policy on the COS.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	HMT21
Name	Ensure that vpxuser password meets length policy.
Description	The default length of the vpxuser password is 32 characters. Ensure that this setting meets your policies; if not, configure to meet password length policies.
Risk or Control	Longer passwords make brute-force password attacks more difficult.
Recommendation Level	DMZ.
Parameters or Objects Configuration	If the password length does not meet your security policies, modify the vpxd. hostPasswordLength parameter in the vpxd.cfg file.

## Host Console

The following sets of recommendations do not pertain to VMware ESX 4.1 (i.e., the “classic” VMware ESX architecture, with the console OS). They apply to only the VMware ESXi architecture.

The direct console user interface (DCUI) is the interface available at the console of a VMware ESXi host (e.g., at the terminal connect to the server) or the iLO, DRAC or other out-of-band management console of the host. It enables basic host configuration—modifying networking settings and the root password, for example—as well as performing maintenance operations such as restarting agents or rebooting the host.

A username and password must be entered to access the DCUI. By default, only the root account has access to the DCUI. Additional accounts can be given access to the DCUI by granting them the local administrator role on the VMware ESXi host.

Lockdown mode is available on any VMware ESXi 4.1 host that you have added to a VMware vCenter Server. Enabling lockdown mode disables all remote access to VMware ESXi 4.1 machines. Any subsequent local changes to the host must be made:

- Using the DCUI. Access to the DCUI is not affected by lockdown mode.
- In a vSphere Client session or using vCLI commands to VMware vCenter Server.

Lockdown mode can be enabled or disabled in two places:

- In the vSphere Client, when connected to the VMware vCenter Server managing the host
- In the DCUI of the host

PARAMETER ELEMENT	DESCRIPTION
Code	HCN02
Name	Enable lockdown mode to restrict remote access.
Description	<p>Lockdown mode can be enabled after a VMware ESXi host is added to VMware vCenter Server. Enabling lockdown mode disables all remote access to VMware ESXi 4.1 machines. Any subsequent local changes to the host must be made:</p> <ul style="list-style-type: none"> <li>• Using the DCUI</li> <li>• In a vSphere Client session or using vCLI commands to VMware vCenter Server</li> </ul> <p>There are some operations, such as backup and troubleshooting, that require direct access to the host. In these cases, lockdown mode can be disabled on a temporary basis for specific hosts as needed, and then reenabled when the task is completed.</p>
Threat	Security best practices dictate that administrative tasks be controlled and monitored from a central location. By forcing all interaction to occur through VMware vCenter Server, the risk of someone's inadvertently attaining elevated privileges or performing tasks that are not properly audited is greatly reduced.
Recommendation Level	Enterprise.
Parameter Setting	To do this manually, in the vSphere Client, in the configuration tab for a host, in the security profile setting, select <b>Lockdown Mode, Edit</b> , and click the checkbox for <b>Lockdown Mode</b> . This can also be done using PowerCLI or with an API client, as well as with VMware Host Profiles. Lockdown mode can also be enabled and disabled from the DCUI.
Effect on Functionality	Enabling lockdown prevents all API-based access by all accounts to the VMware ESXi host. This includes: vSphere Client, vCLI, PowerCLI and any API-based client.

In the extreme case, disabling of all direct access to the host might be desired. For example, you might want to prevent anyone with the root password from disabling lockdown mode and managing the host. In this case, you can take the additional step of disabling the DCUI for the host, through VMware vCenter Server. After this is done, no direct interaction with the host, local or remote, is possible. It can be managed only through VMware vCenter Server. If VMware vCenter Server is down or otherwise unavailable, you cannot revert to direct management, because logging into the DCUI is no longer possible. If the VMware vCenter Server cannot be restored, the only way to revert to direct management is to reinstall the VMware ESXi software on the host.

The following table presents a summary of lockdown mode and its interaction with the various host access services.

ACCESS MODE	NORMAL	LOCKDOWN	LOCKDOWN + DCUI DISABLED
vSphere API (e.g., vSphere client, PowerCLI, vCLI, and so on.)	Any user, based on local roles/privileges	None (except VMware vCenter Server "vpxuser")	None (except VMware vCenter Server "vpxuser")
CIM	Any user, based on local role/privilege	None (except via VMware vCenter Server ticket)	None (except via VMware vCenter Server ticket)
DCUI	Root and users with administrator privileges	Root only	None
Tech Support Mode (local and remote)	Root and users with administrator privileges	None	None

PARAMETER ELEMENT	DESCRIPTION
Code	HCN05
Name	Disable DCUI to prevent all local administrative control.
Description	The DCUI enables simple low-level configuration, such as hostname and root password, as well as diagnostic capabilities such as viewing log files, restarting agents and resetting configurations. To restrict local administrative activity, it can be disabled.
Threat	A user with local administrator role can perform actions directly in the DCUI, and this won't be tracked by VMware vCenter Server. Even if lockdown mode is enabled, someone with the root password can perform administrative tasks in the DCUI. Disabling it prevents local activity and forces actions to be performed in VMware vCenter Server, where they can be centrally audited and monitored.
Recommendation Level	SSLF.
Parameter Setting	To do this manually, in the vSphere Client, in the configuration tab for a host, in the security profile setting, select <b>Properties</b> for <b>Services</b> , highlight <b>DCUI</b> and click <b>Options</b> . The pop-up window will allow you to enable and disable the DCUI service. This can also be done using PowerCLI or with an API client, as well as with VMware Host Profiles. Lockdown mode can also be enabled and disabled from the DCUI.
Effect on Functionality	The DCUI will no longer be accessible. If lockdown mode is enabled, no direct connection to the host will be possible and all interaction must occur through VMware vCenter Server.

On VMware ESXi, Tech Support Mode is a simple shell for advanced technical support. With situations in which remote command-line tools are not capable of addressing some particular issue, Tech Support Mode provides an alternative. Similarly to how the COS is used to execute diagnostic commands and fix certain low-level problems, Tech Support Mode enables users to view log and configuration files, as well as to run certain configuration and utility commands in order to diagnose and fix problems. Tech Support Mode is not based on Linux. Rather, it is a limited-capability shell compiled especially for VMware ESXi.

In VMware ESXi 4.1, Tech Support Mode is fully supported for use by end users and it is enhanced in several ways. In addition to being available on the local console of a host, it can also be accessed remotely through SSH.

Access to Tech Support Mode is controlled in the following ways:

- Both local and remote Tech Support Mode can be enabled and disabled separately in both the DCUI and VMware vCenter Server.
- Tech Support Mode can be used by any authorized user, not just root users. Users become authorized when they are granted the administrator role on a host (through Active Directory membership in a privileged group and through other methods).
- All commands issued in Tech Support Mode are logged through syslog, enabling a full audit trail. If a syslog server is configured, this audit trail is automatically included in the remote logging.
- A timeout can be configured for Tech Support Mode (both local and remote), so that after being enabled, it will automatically be disabled after the configured time.

Tech Support Mode is recommended for use primarily for support, troubleshooting and break-fix situations. It also can be used as part of a scripted installation, as described in the next section. All other uses of Tech Support

To ensure accurate and reliable system logs, you should configure remote syslog on the server, so log messages are kept on an outside system and cannot be altered from the server.

PARAMETER ELEMENT	DESCRIPTION
Code	HCN06
Name	Disable Tech Support Mode unless needed for diagnostics and break-fix.
Description	Tech Support Mode is an interactive command line available only on the console of the server or remotely via SSH. Access to this mode requires the root password of the server. It can be turned on and off for individual hosts, and on a production server should only be turned on if needed to solve a particular troubleshooting issue.
Threat	Anyone logged into Tech Support Mode can assume complete control of the host, including reconfiguring and stealing a virtual machine.
Recommendation Level	Enterprise.
Parameter Setting	<p>Tech Support Mode can be enabled and disabled in one of several ways:</p> <ul style="list-style-type: none"> <li>• On the DCUI of a host, in the <b>Troubleshooting Options</b> menu</li> <li>• With the vSphere Client, on the <b>Configuration</b> tab for a host in the <b>Security Profiles</b> section</li> <li>• Using VMware Host Profiles, management CLI (e.g., PowerCLI) or vSphere API</li> </ul> <p>Local and remote Tech Support Mode must be enabled and disabled independently of one another.</p>
Effect on Functionality	If Tech Support Mode is disabled, supportability and diagnosability of the host might be limited.

PARAMETER ELEMENT	DESCRIPTION
Code	HCN06
Name	Set a timeout for Tech Support Mode.
Description	A timeout can be configured for Tech Support Mode, both local and remote, so that after being enabled, it will automatically be disabled after the configured time. A value of 10 minutes is recommended, although the exact value depends upon the needs of your particular environment.
Threat	If Tech Support Mode is left enabled by accident, it increases the potential for someone to gain privileged access to the host.
Recommendation Level	Enterprise.
Parameter Setting	The timeout for Tech Support Mode can be set in the DCUI, under the <b>Troubleshooting Options</b> menu item.  You can also enable the TSM timeout value in the vSphere Client. On the <b>Configuration</b> tab, select <b>Advanced Settings</b> in the <b>Software</b> section. Find the <code>UserVars.TSMTimeOut</code> parameter and set it to a value between 0 and 86,400 seconds. A value of 0 disables TSM timeout.
Effect on Functionality	If Tech Support Mode is disabled, supportability and diagnosability of the host might be limited.



# vNetwork (Virtual Networking)

## Network Architecture

*NOTE: Unless otherwise indicated, “vSwitch” refers generically to both VMware vNetwork Standard Switches and VMware vNetwork Distributed Switches (Distributed Switches). In the case of Distributed Switches, it is not restricted to any particular vendor.*

Several capabilities of vSphere involve communication among components over a management network.

This includes the following types of communication:

- Between VMware ESX/ESXi and VMware vCenter Server
- Among VMware ESX/ESXi hosts—for example, for VMware High Availability (VMware HA) coordination
- Between VMware ESX/ESXi or VMware vCenter and systems running client software such as the vSphere Client or a vSphere SDK application
- Between VMware ESX/ESXi and ancillary management services, such as DNS, NTP, syslog and the user authentication service
- Between a client system and a privileged virtual machine interface, such as the virtual machine console or the virtual serial port
- Between VMware ESX/ESXi and third-party management tools, such as third-party virtual switch management, hardware monitoring, systems management and backup tools
- Between VMware vCenter Server and supporting services, such as the VMware vCenter Server database and the user authentication service
- Between VMware vCenter Server and optional add-on components such as VMware vCenter Update Manager
- VMware vCenter Converter Enterprise, if they are installed on separate servers
- VMware vMotion, involving transferring the live running state of a virtual machine from one VMware ESX/ESXi host to another
- Storage, including any network-based storage, such as iSCSI and NFS

All of the networks used for these communications provide direct access to core functionality of vSphere. The management network provides access to the vSphere management interface on each component. Any remote attack would most likely begin with gaining entry to this network. vMotion traffic is not encrypted, so the entire state of a virtual machine might potentially be intercepted from this network. Finally, access to the storage network potentially allows someone to read the contents of virtual disks residing on shared storage. Therefore, all of these networks should be isolated and strongly secured from all other traffic, especially any traffic going to and from virtual machines. The exception is if one of the components previously listed actually runs in a virtual machine. In that case, this virtual machine naturally has an interface on the management network and therefore should not have an interface on any other network.

VMware recommends that you isolate networks using one of the following methods:

- Create a separate VLAN for each network.
- Configure network access for each network through its own virtual switch and one or more uplink ports.

In either case, you should consider using network adaptor teaming for the virtual switches to provide redundancy.

If you use VLANs, you need fewer physical network adaptors to provide the isolation, a factor that is especially important in environments with constrained hardware such as blades. VMware virtual switches, by design, are immune to certain types of attacks that have traditionally targeted VLAN functionality. In general, VMware believes that VLAN technology is mature enough that it can be considered a viable option for providing network isolation. The greater risk in using VLANs is that of misconfiguration, in both the virtual network layer and the physical switches.

If you do not use VLANs, either because the VLAN support in your physical network environment is not sufficiently mature or because you do not consider VLANs strong enough for isolation, you can combine the management networks onto one or two virtual switches. However, you should still keep the virtual machine networks separate from the management networks by using separate virtual switches with separate uplinks.

No matter how the management network is restricted, there will always be a need for administrators to access this network to configure VMware vCenter and the VMware ESX/ESXi hosts. Instead of allowing client systems on this network, there are ways to enable access to management functionality in a strictly controlled manner. One way to do this is to configure a controlled gateway or other controlled method to access the management network. For example, require that administrators connect to it via a VPN, and allow access only by trusted administrators.

A more secure way to restrict access to the management network is to configure jump boxes that run vSphere Client and other management clients—for example, VMware vSphere 4 Management Assistant (vSphere Management Assistant). There are different industry-accepted ways to configure a jump box, and the particular method should be chosen based upon a local risk assessment. In one implementation, these systems reside on the management network and do not run any other application. In addition to controlling access to the management network, require that administrators use a remote display protocol (such as RDP or PCoIP) to connect to the jump boxes, and that this access goes through a firewall that restricts network traffic only to this display protocol and any other required to support it. Only the management clients running on the jump boxes are able to manage the vSphere deployment.

If the virtual machines being hosted are going to be accessed only by the same administrators that are accessing the management interfaces, the need to have a separate management network is diminished because the risk is also diminished. For example, if the virtual machines running on a VMware ESX host are all “top secret” in nature, and that is the highest level of classification of virtual machine that will be running on the host, having a separate management network is not necessary. However, if there are different security levels of virtual machines running on the host/cluster (for example, DMZ virtual machines and internal virtual machines, or PCI and non-PCI virtual machines), the management network should be protected at the security level of the most secure virtual machine running on the host/cluster.

CONFIGURATION ELEMENT	DESCRIPTION	
Code	NAR01	
Name	Ensure that vSphere management traffic is on a restricted network.	
Description	The vSphere management network provides access to the vSphere management interface on each component. Any remote attack most likely would begin with gaining entry to this network. The vSphere management interfaces include: <ul style="list-style-type: none"> <li>• Service console interface on VMware ESX</li> <li>• Management VMkernel interface on VMware ESXi</li> </ul>	
Risk or Control	Services running on the management interface provide an opportunity for an attacker to gain privileged access to the systems.	
Recommendation Level	Enterprise.	SSLF.
Parameters or Objects Configuration	The vSphere management port group should be in a dedicated VLAN on a common vSwitch. The vSwitch can be shared with production (virtual machine) traffic, as long as the vSphere management port group's VLAN is not used by production virtual machines.	The vSphere management port group should be on a management-only vSwitch.

CONFIGURATION ELEMENT	DESCRIPTION	
Effect on Functionality		At least one additional physical network adaptor must be dedicated to management (more if network adaptor teaming is used). This might greatly increase the cost of the physical networking infrastructure required. In resource-constrained environments (such as blades), this might not be possible to achieve.
Test	<ul style="list-style-type: none"> <li>• Check for usage of VLAN ID on nonmanagement port groups.</li> <li>• Check that the network segment is not routed, except possibly to networks where other management-related entities are found. In particular, make sure that production virtual machine traffic cannot be routed to this network.</li> </ul>	In addition to enterprise tests, <ul style="list-style-type: none"> <li>• Check that the management-only vSwitch does not contain any nonmanagement port groups.</li> </ul>

CONFIGURATION ELEMENT	DESCRIPTION	
Code	NAR02	
Name	Ensure that vMotion traffic is isolated.	
Description	The security issue with vMotion migrations is that information is transmitted in plain text, and anyone with access to the network over which this information flows can view it. Ensure that vMotion traffic is separate from production traffic on an isolated network. This network should be nonroutable (no layer-3 router spanning this and other networks), which will prevent any outside access to the network.	
Risk or Control	Attackers can intercept vMotion traffic to obtain memory contents of a virtual machine. They might also potentially stage a MiTM attack in which the contents are modified during migration.	
Recommendation Level	Enterprise.	SSLF.
Parameters or Objects Configuration	The vMotion port group should be in a dedicated VLAN on a common vSwitch. The vSwitch can be shared with production (virtual machine) traffic, as long as the vMotion port group's VLAN is not used by production virtual machines.	The vMotion port group should be on a management-only vSwitch.

CONFIGURATION ELEMENT	DESCRIPTION	
Effect on Functionality		At least one additional physical network adaptor must be dedicated to management (more if network adaptor teaming is used). This might greatly increase the cost of the physical networking infrastructure required. In resource-constrained environments (such as blades), this might not be possible to achieve.
Test	<ul style="list-style-type: none"> <li>• Check for usage of the VLAN ID on non-vMotion port groups.</li> <li>• Check that the VLAN is isolated and not routed in the physical network.</li> </ul>	In addition to enterprise tests: <ul style="list-style-type: none"> <li>• Check that the vMotion port group vSwitch does not contain any nonmanagement port groups.</li> <li>• Check that the physical network is not accessed by any other nonmanagement entity.</li> </ul>

CONFIGURATION ELEMENT	DESCRIPTION	
Code	NAR03	
Name	Ensure that IP-based storage traffic is isolated.	
Description	Virtual machines might share virtual switches and VLANs with the IP-based storage configurations. IP-based storage includes: <ul style="list-style-type: none"> <li>• iSCSI</li> <li>• NFS</li> </ul> This type of configuration might expose IP-based storage traffic to unauthorized virtual machine users. To restrict unauthorized users from viewing the IP-based storage traffic, the IP-based storage network should be logically separated from the production traffic. Configuring the IP-based storage adaptors on separate VLANs or network segments from the VMkernel management and service console network will limit unauthorized users from viewing the traffic.	
Risk or Control	IP-based storage frequently is not encrypted. It can be viewed by anyone with access to this network.	
Recommendation Level	Enterprise.	SSLF.
Parameters or Objects Configuration	Storage port groups should be in a dedicated VLAN on a common vSwitch. The vSwitch can be shared with production (virtual machine) traffic, as long as the storage port group's VLAN is not used by production virtual machines.	The storage port group should be on a management-only vSwitch.

CONFIGURATION ELEMENT	DESCRIPTION	
Effect on Functionality		At least one additional physical network adaptor must be dedicated to management (more if network adaptor teaming is used). This might greatly increase the cost of the physical networking infrastructure required. In resource-constrained environments (such as blades), this might not be possible to achieve.
Test	<ul style="list-style-type: none"> <li>• Check for usage of the VLAN ID on non-storage port groups.</li> <li>• Check that the VLAN is isolated and not routed in the physical network.</li> </ul>	In addition to enterprise tests, <ul style="list-style-type: none"> <li>• Check that the storage port group vSwitch does not contain any nonmanagement port groups.</li> <li>• Check that the physical network is not accessed by any other nonmanagement entity.</li> </ul>

OPERATIONAL ELEMENT	DESCRIPTION	
Code	NAR04	
Name	Strictly control access to the management network.	
Description	<p>The management network should be protected at the security level of the most secure virtual machine running on a host/cluster.</p> <p>No matter how the management network is restricted, there will always be a need for administrators to access this network to configure VMware vCenter Server and the VMware ESX/ESXi hosts. Instead of allowing client systems on this network, there are ways to enable access to management functionality in a strictly controlled manner.</p>	
Risk or Control	If an attacker gains access to the management network, it provides the staging ground for further attack.	
Recommendation Level	Enterprise.	DMZ.
Condition or Steps	Configure a controlled gateway or other controlled method to access the management network. For example, require that administrators connect to it via a VPN, and allow access only by trusted administrators.	Configure jump boxes that run vSphere Client and other management clients (e.g., vSphere Management Assistant). There are different industry-accepted ways to configure a jump box. The particular method should be chosen based upon a local risk assessment.

## vNetwork Configuration

Port groups define how virtual machine connections are made through the virtual switch. They can be configured with bandwidth limitations and VLAN tagging policies for each member port. Multiple ports can be aggregated under port groups to provide a local point for virtual machines to connect to a network. The maximum number of port groups that can be configured on a virtual switch is 512. A network label and optionally a VLAN ID identify each port group.

CONFIGURATION ELEMENT	DESCRIPTION
Code	NCN02
Name	Ensure that there are no unused ports on a distributed vSwitch port group.
Description	The number of ports in a distributed port group can be adjusted to exactly match the number of virtual machines assigned to that port group.
Risk or Control	Limiting the number of ports in a port group limits the potential for a virtual machine administrator, either accidentally or maliciously, to move a virtual machine to an unauthorized network. This is especially relevant if the management network is on a distributed switch, because it might help prevent someone from putting a rogue virtual machine on this network.
Recommendation Level	DMZ.
Parameters or Objects Configuration	<b>Number of Ports</b> setting in the settings page of a port group.
Test	Can be done manually through the vSphere Client. 1.While connected to the VMware vCenter Server: Navigate to Home → Inventory → Networking in the vSphere Client and click the vDS in question. 2.Click the <b>Ports</b> tab. 3.Check if all of the ports in the list have a virtual machine associated with them in the <b>connected</b> column. The equivalent steps can be automated using scripting or the SDK.

Each virtual network adaptor in a virtual machine has an initial MAC address assigned when the virtual adaptor is created. Each virtual adaptor also has an effective MAC address that filters out incoming network traffic with a destination MAC address different from the effective MAC address. A virtual adaptor's effective MAC address and initial MAC address are the same when they are initially created. However, the virtual machine's operating system might alter the effective MAC address to another value at any time. If the virtual machine operating system changes the MAC address, the operating system can send frames with an impersonated source MAC address at any time. This allows an operating system to stage malicious attacks on the devices in a network by impersonating a network adaptor authorized by the receiving network. System administrators can use virtual switch security profiles on VMware ESX server hosts to protect against this type of attack by setting two options on virtual switches. These options are MAC "address changes" and "forged transmits."

MAC address changes are set to "accept" by default, meaning that the virtual switch accepts requests to change the effective MAC address. The MAC "address changes" setting affects traffic received by a virtual machine. To protect against MAC impersonation, this option will be set to "reject," ensuring that the virtual switch does not honor requests to change the effective MAC address to anything other than the initial MAC address. Setting this to "reject" disables the port that the virtual network adaptor used to send the request. The virtual network adaptor does not receive any more frames until it configures the effective MAC address to match the initial MAC address. The guest operating system will not detect that the MAC address change has not been honored.

Forged transmissions are set to accept by default. This means the virtual switch does not compare the source and effective MAC addresses. The "forged transmits" setting affects traffic transmitted from a virtual machine. If this option is set to "reject," the virtual switch compares the source MAC address being transmitted by the operating system with the effective MAC address for its virtual network adaptor, to see if they are the same.

If the MAC addresses are different, the virtual switch drops the frame. The guest operating system will not detect that its virtual network adaptor cannot send packets using the different MAC address. To protect against MAC address impersonation, all virtual switches should have “forged transmissions” set to “reject.”

VMware ESX server has the ability to run virtual and physical network adaptors in promiscuous mode. Promiscuous mode can be enabled on public and private virtual switches. When it is enabled for a public virtual switch, all virtual machines connected to the public virtual switch have the potential of reading all packets sent across that network, from other virtual machines and any physical machines or other network devices. When it is enabled for a private virtual switch, all virtual machines connected to the private virtual switch have the potential of reading all packets across that network, meaning only the virtual machines connected to that private virtual switch. By default, promiscuous mode is set to “reject,” meaning that the virtual network adaptor cannot operate in promiscuous mode.

These parameters can be set on a per-vSwitch basis. They can also be overridden on individual port groups. This is how exceptions should be made for special virtual machines that require these capabilities, such as inline virtual security devices or clustering software.

PARAMETER ELEMENT	DESCRIPTION
Code	NCN03
Name	Ensure that the “MAC Address Change” policy is set to “reject.”
Description	To protect against MAC impersonation, this option should be set to “reject,” ensuring that the virtual switch does not honor requests to change the effective MAC address to anything other than the initial MAC address.
Threat	If the virtual machine operating system changes the MAC address, it can send frames with an impersonated source MAC address at any time. This allows it to stage malicious attacks on the devices in a network by impersonating a network adaptor authorized by the receiving network.
Recommendation Level	Enterprise.
Parameter Setting	MAC address changes set to “reject” (“accept” by default) on all vSwitches.
Effect on Functionality	This will prevent virtual machines from changing their effective MAC address. It will affect applications that require this functionality. An example of such an application is Microsoft Clustering, which requires systems to effectively share a MAC address. This will also affect how a layer-2 bridge will operate. VMware vShield Zones will not operate properly if the “MAC Address Change” is set to “reject.” This will also affect applications that require a specific MAC address for licensing. An exception should be made for the port groups that these applications are connected to.

PARAMETER ELEMENT	DESCRIPTION
Code	NCN04
Name	Ensure that the “Forged Transmits” policy is set to “reject.”
Description	Forged transmissions should be set to “accept” by default. This means the virtual switch does not compare the source and effective MAC addresses. To protect against MAC address impersonation, all virtual switches should have forged transmissions set to “reject.”

PARAMETER ELEMENT	DESCRIPTION
Threat	If the virtual machine operating system changes the MAC address, the operating system can send frames with an impersonated source MAC address at any time. This allows an operating system to stage malicious attacks on the devices in a network by impersonating a network adaptor authorized by the receiving network.
Recommendation Level	Enterprise.
Parameter Setting	"Forged Transmits" parameter should be set to "reject" on all vSwitches.
Effect on Functionality	This will prevent virtual machines from changing their effective MAC address. This will affect applications that require this functionality. An example of such an application is Microsoft Clustering, which requires systems to effectively share a MAC address. This will also affect how a layer-2 bridge will operate. VMware vShield Zones will not operate properly if the "Forged Transmits" parameter is set to "reject." This will also affect applications that require a specific MAC address for licensing. An exception should be made for the port groups that these applications are connected to.

PARAMETER ELEMENT	DESCRIPTION
Code	NCN05
Name	Ensure that the "Promiscuous Mode" policy is set to "reject."
Description	Promiscuous mode is disabled by default on the VMware ESX server. This is the recommended setting. However, there might be a legitimate reason to enable it for debugging, monitoring or troubleshooting reasons.
Threat	When promiscuous mode is enabled for a private virtual switch, all virtual machines connected to the private virtual switch have the potential of reading all packets across that network, meaning only the virtual machines connected to that private virtual switch.
Recommendation Level	Enterprise.
Parameter Setting	"Promiscuous Mode" parameter should be set to "reject" on all vSwitches.
Effect on Functionality	VMware vShield Zones and other security devices that require the ability to see all packets on a vSwitch will not operate properly if the "Promiscuous Mode" parameter is set to "reject." An exception should be made for the port groups that these applications are connected to, in order to allow for full-time visibility to the traffic on that virtual switch.

Physical switches use the native VLAN for switch control and management protocol. Native VLAN frames are not tagged with any VLAN ID in many types of switches. The trunk ports implicitly treat all untagged frames as native VLAN frames. VLAN 1 is the default native VLAN ID for many commercial switches. However, in many enterprise networks, the native VLAN might be VLAN 1 or any number, depending on the switch type.



PARAMETER ELEMENT	DESCRIPTION
Code	NCN06
Name	Ensure that port groups are not configured to the value of the native VLAN.
Description	<p>VMware ESX does not use the concept of native VLAN. Frames with VLAN specified in the port group will have a tag. Frames with VLAN not specified in the port group are not tagged and therefore will end up belonging to the native VLAN of the physical switch.</p> <p>For example, frames on VLAN 1 from a Cisco physical switch will be untagged, because this is considered as the native VLAN. However, frames from VMware ESX specified as VLAN 1 will be tagged with a "1." Therefore, traffic from VMware ESX that is destined for the native VLAN will not be correctly routed (because it is tagged with a "1" instead of being untagged). Traffic from the physical switch coming from the native VLAN will not be visible (because it is not tagged).</p>
Risk or Control	If the VMware ESX virtual switch port group uses the native VLAN ID, traffic from those virtual machines will not be visible to the native VLAN on the switch, because the switch is expecting untagged traffic.
Recommendation Level	Enterprise.
Parameters Setting	If the default value of 1 for the native VLAN is being used, the VMware ESX server virtual switch port groups should be configured with any value between 2 and 4094. Otherwise, ensure that the port group is <b>not</b> configured to use whatever value is set for the native VLAN.

PARAMETER ELEMENT	DESCRIPTION
Code	NCN07
Name	Ensure that port groups are not configured to VLAN 4,095 except for virtual guest tagging (VGT).
Description	When a port group is set to VLAN 4095, this activates VGT mode. In this mode, the vSwitch passes all network frames to the guest virtual machine without modifying the VLAN tags, leaving it for the guest to interact with them. VLAN 4095 should be used only if the guest has been specifically configured to manage VLAN tags.
Risk or Control	If VGT is enabled inappropriately, it might cause denial of service or allow a guest virtual machine to interact with traffic on an unauthorized VLAN.
Recommendation Level	Enterprise.
Parameters Setting	The VLAN ID setting on all port groups should not be set to 4095 unless VGT is required.

PARAMETER ELEMENT	DESCRIPTION
Code	NCN08
Name	Ensure that port groups are not configured to VLAN values reserved by upstream physical switches.
Description	Certain physical switches reserve certain VLAN IDs for internal purposes and often disallow traffic configured to these values. For example, Cisco Catalyst switches typically reserve VLANs 1001-1024 and 4094, while Nexus switches typically reserve 3968-4047 and 4094. Check with the documentation for your specific switch.
Risk or Control	Using a reserved VLAN might result in a denial of service on the network.
Recommendation Level	Enterprise.
Parameters Setting	The VLAN ID setting on all port groups should not be set to reserved values of the physical switch.

OPERATIONAL ELEMENT	DESCRIPTION
Code	NCN10
Name	Ensure that port groups are configured with a clear network label.
Description	A network label identifies each port group with a name. These names are important because they serve as a functional descriptor for the port group.
Risk or Control	Without these descriptions, identifying port groups and their functions becomes difficult as the network becomes more complex.
Recommendation Level	Enterprise.
Condition or Steps	This can be done through the vSphere Client by manually checking the names of the different port groups. To check the port group names in the vSphere Client, connect to the VMware vCenter Server and navigate to Home → Inventory → Networking. You will be able to view all the different port groups and determine whether the port group names are clearly labeled or might be renamed with a meaningful name.  Scripted method (vCLI command): vicfg-vswitch -l command.

OPERATIONAL ELEMENT	DESCRIPTION
Code	NCN11
Name	Ensure that all vSwitches have a clear network label.
Description	Virtual switches within the VMware ESX server require a field for the name of the switch. This label is important because it serves as a functional descriptor for the switch, just as physical switches require a host name.

OPERATIONAL ELEMENT	DESCRIPTION
Risk or Control	Labeling virtual switches will indicate the function or the IP subnet of the virtual switch. For instance, labeling the virtual switch as "internal" or some variation will indicate that the virtual switch is only for internal networking through a virtual machine's private virtual switch, with no physical network adaptors bound to it.
Recommendation Level	Enterprise.
Condition or Steps	<p>This can be done through the vSphere Client by manually checking the names of the different vSwitches. To check the port group names in the vSphere Client, connect to the VMware vCenter Server and navigate to Home → Inventory → Networking. You will be able to view all the different vSwitches and determine whether the port group names are clearly labeled or might be renamed with a meaningful name.</p> <p>Scripted method (vCLI command): vicfg-vswitch -l command.</p>

OPERATIONAL ELEMENT	DESCRIPTION
Code	NCN12
Name	Fully document all VLANs used on vSwitches.
Description	When defining a physical switch port for trunk mode, care must be taken to ensure that only specified VLANs are configured. It is considered best practice to restrict to only those VLANs required on the VLAN trunk link.
Risk or Control	The risk of not fully documenting all VLANs on the vSwitch is that it is possible that a physical trunk port might be configured without needed VLANs, or with unneeded VLANs, potentially enabling an administrator to either accidentally or maliciously connect a virtual machine to an unauthorized VLAN.
Recommendation Level	Enterprise.
Condition or Steps	<p>Both standard and distributed vSwitch configurations can be viewed in the vSphere Client or by using the vSphere API.</p> <p>For a standard vSwitch, vicfg-vswitch -l will list all port groups and their VLAN association. Compare this list with the physical switch configuration.</p>

OPERATIONAL ELEMENT	DESCRIPTION
Code	NCN13
Name	Ensure that only authorized administrators have access to virtual networking components.

OPERATIONAL ELEMENT	DESCRIPTION
Description	It is important to leverage the role-based access controls within vSphere to ensure that only authorized administrators have access to the different virtual networking components. For example, virtual machine administrators should have access only to port groups in which their virtual machines reside. Network administrators should have permissions to all virtual networking components but not have access to virtual machines. These controls will depend very much on the organization's policy on separation of duties, least privilege, and the responsibilities of the administrators within the organization.
Risk or Control	This control mitigates the risk of misconfiguration, whether accidental or malicious, and enforces key security concepts of separation of duties and least privilege.
Recommendation Level	Enterprise.
Condition or Steps	Ensure that vSphere permissions to specific port groups are granted only to those individuals who need it.

## Physical Network

OPERATIONAL ELEMENT	DESCRIPTION
Code	NPN01
Name	Ensure that physical switch ports are configured with spanning tree disabled.
Description	EST mode has a one-to-one relationship. The number of VLANs supported on the VMware ESX server system is limited to the number of physical network adaptor ports assigned to the VMkernel. EST is enabled when the port group's VLAN ID is set to 0 or left blank. Due to the integration of the VMware ESX server into the physical network, the physical network adaptors must have spanning tree disabled or portfast configured for external switches, because VMware virtual switches do not support STP. Virtual switch uplinks do not create loops within the physical switch network.
Risk or Control	If these are not set, potential performance and connectivity issues might arise.
Recommendation Level	Enterprise.
Condition or Steps	Log in to the physical switch and ensure that spanning tree protocol is disabled and/or portfast is configured for all physical ports connected to VMware ESX/ESXi hosts.

OPERATIONAL ELEMENT	DESCRIPTION
Code	NPN02
Name	Ensure that the <i>non-negotiate</i> option is configured for trunk links between external physical switches and virtual switches in VST mode.
Description	In order to communicate with virtual switches in VST mode, external switch ports must be configured as trunk ports. VST mode does not support dynamic trunking protocol (DTP), so the trunk must be static and unconditional. The auto or desirable physical switch settings do not work with the VMware ESX server because the physical switch communicates with the VMware ESX server using DTP. The <i>non-negotiate</i> and <i>on</i> options unconditionally enable VLAN trunking on the physical switch and create a VLAN trunk link between the VMware ESX server and the physical switch. The difference between <i>non-negotiate</i> and <i>on</i> options is that <i>on</i> mode still sends out DTP frames, whereas the <i>non-negotiate</i> option does not.
Risk or Control	The <i>non-negotiate</i> option should be used for all VLAN trunks, to minimize unnecessary network traffic for virtual switches in VST mode.
Recommendation Level	Enterprise.
Condition or Steps	Log in to the physical switch and ensure that DTP is not enabled on the physical switch ports connected to the VMware ESX/ESXi host.

OPERATIONAL ELEMENT	DESCRIPTION
Code	NPN03
Name	Ensure that VLAN trunk links are connected only to physical switch ports that function as trunk links.
Description	When connecting a virtual switch to a VLAN trunk port, you must be careful to properly configure both the virtual switch and the physical switch at the uplink port. If the physical switch is not properly configured, frames with the VLAN 802.1q header would be forwarded to a switch not expecting their arrival. The vSphere administrator should always ensure that virtual switch uplinks, acting as VLAN trunk links, are connected only to physical switch ports that function as trunk links.
Risk or Control	Misconfiguration of the physical switch ports might lead to undesirable performance, including frames being dropped or misdirected.
Recommendation Level	Enterprise.
Condition or Steps	Routinely check physical switch ports to ensure that they are properly configured as trunk ports.

## VMware vCenter

### VMware vCenter Server Host

Because VMware vCenter Server runs on a Windows host, it is especially critical to protect this host against vulnerabilities and attacks. The standard set of recommendations applies, as it would for any host: Install antivirus agents, spyware filters, intrusion detection systems and any other security measures. Make sure to keep all security measures up to date, including application of patches.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSH01
Name	Maintain supported operating system, database and hardware for VMware vCenter.
Description	VMware vCenter Server resides on a Windows-based operating system and therefore requires a supported version of Windows.
Risk or Control	If VMware vCenter is not running on a supported OS, it might not run properly. An attacker might be able to take advantage of this to perform a DoS attack or worse.
Recommendation Level	Enterprise.
Condition or Steps	For OS and database compatibility, see the <i>vSphere Compatibility Matrixes</i> white paper: <a href="http://www.vmware.com/pdf/vsphere4/r40/vsp_compatibility_matrix.pdf">http://www.vmware.com/pdf/vsphere4/r40/vsp_compatibility_matrix.pdf</a>  For hardware requirements, see the <i>VMware ESX and VMware vCenter Server Installation Guide</i> white paper: <a href="http://www.vmware.com/pdf/vsphere4/r40/vsp_40_esx_vc_installation_guide.pdf">http://www.vmware.com/pdf/vsphere4/r40/vsp_40_esx_vc_installation_guide.pdf</a>

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSH02
Name	Keep VMware vCenter Server system properly patched.
Description	By staying up to date on Windows patches, vulnerabilities in the OS can be mitigated.
Risk or Control	If an attacker can obtain access and elevate privileges on the VMware vCenter Server system, they can then take over the entire vSphere deployment.
Recommendation Level	Enterprise.
Condition or Steps	Employ a system to keep the VMware vCenter Server system up to date with patches in accordance with industry-standard guidelines, or internal guidelines where appropriate.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSH03
Name	Provide Windows system protection on the VMware vCenter Server host.
Description	By providing OS-level protection, vulnerabilities in the OS can be mitigated. This protection includes antivirus, antimalware and similar measures.
Risk or Control	If an attacker can obtain access and elevate privileges on the VMware vCenter Server system, they can then take over the entire vSphere deployment.
Recommendation Level	Enterprise.
Condition or Steps	Provide Windows system protection, such as antivirus, in accordance with industry-standard guidelines, or internal guidelines where appropriate.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSH04
Name	Avoid user login to VMware vCenter Server system.
Description	After someone has logged in to the VMware vCenter Server system, it becomes more difficult to prevent what they can do. In general, logging in to the VMware vCenter Server system should be limited to very privileged administrators, and then only for the purpose of administering VMware vCenter Server or the host OS.
Risk or Control	Anyone logged in to the VMware vCenter Server can potentially cause harm, either intentionally or unintentionally, by altering settings and modifying processes. They also have potential access to VMware vCenter credentials, such as the SSL certificate.
Recommendation Level	Enterprise.
Condition or Steps	Restrict login to the VMware vCenter System to only those personnel who have legitimate tasks to perform in it. Ensure that they log in only when necessary, and audit these events.

CONFIGURATION ELEMENT	DESCRIPTION
Code	VSH05
Name	Install VMware vCenter Server using a service account instead of a built-in Windows account.

CONFIGURATION ELEMENT	DESCRIPTION
Description	<p>You can use the Microsoft Windows built-in system account or a user account to run VMware vCenter Server. With a user account, you can enable Windows authentication for SQL Server.</p> <p>It also provides more security.</p> <p>The user account must be an administrator on the local machine. In the installation wizard, you specify the account name as DomainName\Username. If you are using SQL Server for the VMware vCenter database, you must configure the SQL Server database to allow the domain account access to SQL Server.</p> <p>Even if you do not plan to use Microsoft Windows authentication for SQL Server, or if you are using an Oracle database, you might want to set up a local user account for the VMware vCenter Server system. In this case, the only requirement is that the user account must be an administrator on the local machine.</p>
Risk or Control	The Microsoft Windows built-in system account has more permissions and rights on the server than the VMware vCenter Server system requires, which can contribute to security problems.
Recommendation Level	DMZ.
Parameters or Objects Configuration	Before installing VMware vCenter Server, create a special-purpose user account on the Windows host and grant it only to the local administrator role on the host. This account should have "Act as part of the operating system" privilege, and write access to the local file system. Specify this account in the VMware vCenter Server installation process.
Test	<ul style="list-style-type: none"> <li>• Check to see that the VMware vCenter processes are running as the service account.</li> <li>• Check to make sure that the service account has only local administrator role.</li> </ul>

CONFIGURATION ELEMENT	DESCRIPTION
Code	VSH06
Name	Restrict usage of vSphere administrator privilege.
Description	By default, VMware vCenter Server grants full administrative rights to the local administrator's account, which can be accessed by domain administrators.
Risk or Control	Separation of duties dictates that full vSphere administrative rights should be granted only to those administrators who are required to have it. This privilege should not be granted to any group whose membership is not strictly controlled. Therefore, administrative rights should be removed from the local Windows administrator account and instead be given to a special-purpose local vSphere administrator account.
Recommendation Level	Enterprise. DMZ.



CONFIGURATION ELEMENT	DESCRIPTION	
Condition or Steps	<ol style="list-style-type: none"> <li>1. Create an ordinary user account that will be used to manage VMware vCenter (example vi-admin).</li> <li>2. Make sure the user does not belong to any local groups, such as administrator.</li> <li>3. Log on to VMware vCenter as the Windows administrator. Then grant the role of administrator (global VMware vCenter administrator) to the account created in step 1 on the top-level hosts and clusters folder.</li> <li>4. Log out of VMware vCenter and log into VMware vCenter with the account created in step 1. Verify that user is able to perform all tasks available to a VMware vCenter administrator.</li> <li>5. Remove the permissions in the VMware vCenter for the local administrator</li> </ol>	<p>After performing the steps in the “enterprise” level, protect the vi-admin account from regular usage and instead rely upon accounts tied to specific individuals. This should be done as follows:</p> <ol style="list-style-type: none"> <li>1. Logged in as vi-admin, grant full administrative rights to the minimum number of individuals required, typically senior IT staff.</li> <li>2. Log out as vi-admin, and then protect the password.</li> </ol> <p>There are numerous ways in which the password can be protected. For example, use a very strong password and then lock the printout in a safe, or employ a system by which two individuals each must type one half of a password, the other half of which is mutually unknown by the other individual.</p>
Test	Observe the assigned permissions in vSphere. Make sure that “Administrator” or any other account or group does not have any privileges.	

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSH07
Name	Check for privilege reassignment after VMware vCenter Server restarts
Description	<p>During a restart of VMware vCenter Server, if the user or user group that is assigned administrator role on the root folder cannot be verified as a valid user/group during the restart, the user’s/group’s permission as administrator will be removed. In its place, VMware vCenter Server grants the administrator role to the local Windows administrators group, to act as a new VMware vCenter Server administrator.</p> <p>Because it is not recommended to grant VMware vCenter Server administrator rights to Windows administrators, this results in a situation that should be rectified by reestablishing a legitimate administrator account.</p>

OPERATIONAL ELEMENT	DESCRIPTION
Risk or Control	Separation of duties dictates that full vSphere administrative rights should be granted only to those administrators who are required to have it. This privilege should not be granted to any group whose membership is not strictly controlled. Therefore, administrative rights should be removed from the local Windows administrator account and instead be given to a special-purpose local vSphere administrator account.
Recommendation Level	Enterprise.
Condition or Steps	Anytime that VMware vCenter Server restarts, the log file should be scanned to ensure that no privileges were reassigned.  For the location of VMware vCenter Server log files, see this VMware knowledge base article: <a href="http://kb.vmware.com/kb/1021804">http://kb.vmware.com/kb/1021804</a> .

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSH10
Name	Clean up log files after failed installations of VMware vCenter Server.
Description	In certain cases, if the VMware vCenter installation fails, a log file (with a name of the form "hs_err_pidXXXX") is created that contains the database password in plain text.
Risk or Control	An attacker who breaks into the VMware vCenter Server might potentially steal this password and access the VMware vCenter database.
Recommendation Level	Enterprise.
Condition or Steps	If at any time a VMware vCenter Server installation fails, the log files should be deleted securely before putting the host into production. For the location of VMware vCenter Server log files, see this VMware knowledge base article: <a href="http://kb.vmware.com/kb/1021804">http://kb.vmware.com/kb/1021804</a> .

## vCenter Server Communication

Client sessions with VMware vCenter Server can be initiated from any vSphere API client, such as vSphere Client and PowerCLI. By default, SSL encryption protects this connection, but the default certificates are not signed by a trusted certificate authority and do not provide the authentication security you might need in a production environment. These self-signed certificates are vulnerable to MiTM attacks, and clients receive a warning about them. If you intend to use encrypted remote connections externally, consider purchasing a certificate from a trusted certificate authority or use your own security certificate for your SSL connections.

Certificates are currently stored in C:\Documents and Settings\All Users\Application Data\VMware\VMware VirtualCenter\SSL\. By default, these can be accessed by any user on the server.

CONFIGURATION ELEMENT	DESCRIPTION
Code	VSC01
Name	Do not use default self-signed certificates.
Description	Self-signed certificates are automatically generated by VMware vCenter Server during the installation process, are not signed by a commercial CA, and might not provide strong security. Replace default self-signed certificates with those from a trusted certification authority, either a commercial CA or an organizational CA.
Risk or Control	The use of default certificates leaves the SSL connection open to MiTM attacks. Changing the default certificates to trusted CA-signed certificates mitigates the potential for MiTM attacks.
Recommendation Level	Enterprise.
Condition or Steps	For instructions on how to change self-signed certificates, see the <i>Replacing vCenter Server Certificates</i> white paper: <a href="http://www.vmware.com/resources/techresources/10124">http://www.vmware.com/resources/techresources/10124</a>
Test	Ensure that any certificates presented by the host can be verified by a trusted certification authority.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSC02
Name	Monitor access to SSL certificates.
Description	The directory that contains the SSL certificates only needs to be accessed by the service account user on a regular basis. Occasionally, the VMware vCenter Server system administrator might need to access it for support purposes.
Risk or Control	The SSL certificate can be used to impersonate VMware vCenter and decrypt its database password.
Recommendation Level	DMZ.
Condition or Steps	Use event log monitoring to alert on nonservice account access to certificates directory.

PARAMETER ELEMENT	DESCRIPTION
Code	VSC03
Name	Restrict access to SSL certificates.
Description	By default, any user on the VMware vCenter Server system can access the directory containing the SSL certificates. The directory that contains the SSL certificates only needs to be accessed by the service account user on a regular basis. Occasionally, when collecting data for support purposes, the VMware vCenter Server system administrator might need to access it.
Threat	The SSL certificate can be used to impersonate VMware vCenter and decrypt its database password.
Recommendation Level	SSLF.
Parameter Setting	Change the Windows file permission on the SSL certificate directory so that only the VMware vCenter service account can access it.
Effect on Functionality	Supportability limitations: <ul style="list-style-type: none"> <li>• Will prevent a complete support log from being collected when the vc-support script is issued</li> <li>• Will prevent the administrator from being able to change the VMware vCenter database password</li> </ul>

OPERATIONAL ELEMENT	DESCRIPTION
Code	VSC04
Name	Always verify SSL certificates.
Description	When connecting to VMware vCenter Server using vSphere Client, the client checks to see if the certificate being presented can be verified by a trusted third party. If it cannot be, the user is presented with a warning and the option to ignore this check. This warning should not be ignored. If an administrator is presented with this warning, they should inquire further about it before proceeding.
Risk or Control	Without certificate verification, the user can be subject to a MiTM attack, which potentially might enable compromise through impersonation with the user's credentials to the VMware vCenter Server system.
Recommendation Level	Enterprise.
Condition or Steps	Instruct any user of vSphere Client to never ignore certificate verification warnings.

The only network connection that VMware vCenter Server requires is to the management network described in the vNetwork section. Avoid putting the VMware vCenter Server system on any other network, such as your production or storage network, or on a network with access to the public Internet. Specifically, VMware vCenter Server does not need access to the network on which vMotion operates. By limiting the network connectivity, you cut down on the possible avenues of attack.

In general, VMware vCenter Server needs network connectivity only to the following systems:

- All VMware ESX/ESXi hosts
- The VMware vCenter Server database
- Other VMware vCenter Server systems, if operating in linked mode
- Systems that are authorized to run management clients

Examples of these include:

- vSphere Client
- vSphere Management Assistant
- A Windows system from which the PowerCLI is to be used
- Any other vSphere Web Services SDK-based client
- Systems running add-on components, such as VMware vCenter Update Manager
- IT infrastructure services, such as DNS, AD, NTP, and so on
- Other systems running components essential to any particular functionality of VMware vCenter Server that is needed

Use the following guidelines to limit network connectivity:

CONFIGURATION ELEMENT	DESCRIPTION
Code	VSC05
Name	Restrict network access to VMware vCenter Server system.
Description	Restrict access to only those essential components required to communicate with VMware vCenter.
Risk or Control	Blocking access by unnecessary systems mitigates general attacks on the Windows system.
Recommendation Level	DMZ.
Parameters or Objects Configuration	You should protect the VMware vCenter Server by using a local firewall on the Windows system of VMware vCenter or a network firewall. This protection should include IP-based access restrictions, so that only necessary components can communicate with the VMware vCenter Server system.
Test	

CONFIGURATION ELEMENT	DESCRIPTION
Code	VSC06
Name	Block access to ports not being used by VMware vCenter.
Description	A local firewall on the Windows system of VMware vCenter, or a network firewall, can be used to block access to ports not specifically being used by VMware vCenter.
Risk or Control	Blocking unneeded ports can mitigate general attacks on the Windows system.
Recommendation Level	DMZ.

CONFIGURATION ELEMENT	DESCRIPTION
Parameters or Objects Configuration	<p>A list of ports used by VMware vCenter can be found in this VMware knowledge base article: <a href="http://kb.vmware.com/kb/1012382">http://kb.vmware.com/kb/1012382</a>.</p> <p>Here is a partial list of examples of where ports might be blocked:</p> <ul style="list-style-type: none"> <li>• 636/TCP: If the VMware vCenter will not be part of a linked-mode VMware vCenter group</li> <li>• 1521/TCP: If the VCDB is not Oracle</li> </ul> <p>Make sure not to block any ports for functionality that is actually in use in your environment.</p>
Test	

PARAMETER ELEMENT	DESCRIPTION
Code	VSC07
Name	Disable managed object browser.
Description	The managed object browser provides a way to explore the object model used by the VMware vCenter to manage the vSphere environment. It enables configurations to be changed as well. This interface is used primarily for debugging the vSphere Web Services SDK.
Threat	This interface might potentially be used to perform malicious configuration changes or actions.
Recommendation Level	DMZ.
Parameter Setting	To disable the managed object browser, edit the vpxd.cfg file and ensure that the following element is set: <enableDebugBrowse>false<enableDebugBrowse/> This should be the only occurrence of this element, and it should be within the <vpxd> ... </vpxd> element in vpxd.cfg
Effect on Functionality	The managed object browser will no longer be available for diagnostics.

PARAMETER ELEMENT	DESCRIPTION
Code	VSC08
Name	Disable vSphere Web Access.

PARAMETER ELEMENT	DESCRIPTION
Description	<p>vSphere Web Access provides a means for users to view virtual machines and perform simple operations such as power-on and suspend. It also provides a way to obtain console access to virtual machines. All of this is governed by the user permissions on VMware vCenter Server.</p> <p>In some cases, you might want to disable vSphere Web Access to eliminate the risk of having an open interface that is not being used.</p>
Threat	This is a Web interface and therefore has some of the general risks associated with all Web interfaces.
Recommendation Level	DMZ.
Parameter Setting	<p>To completely delete the vSphere Web Access service from VMware vCenter Server:</p> <ol style="list-style-type: none"> <li>1. Select <b>Start &gt; Programs &gt; Administrative Tools &gt; Services</b>.</li> <li>2. Stop the VMware VirtualCenter Management Webservices service.</li> <li>3. Use Windows Explorer to open C:\Program Files\VMware\Infrastructure\tomcat\webapps and delete the ui directory.</li> <li>4. (Optional) Use Windows Explorer to open C:\Program Files\VMware\Infrastructure\tomcat\work\Catalina\localhost and delete the ui directory.</li> <li>5. Start the VMware VirtualCenter Management Webservices service.</li> </ol> <p>See VMware knowledge base article 1009420 for more details.</p> <p><i>NOTE: Any upgrade to VMware vCenter Server will recreate this file.</i></p>
Effect on Functionality	vSphere Web Access will no longer be available.

PARAMETER ELEMENT	DESCRIPTION
Code	VSC09
Name	Disable datastore browser.
Description	<p>The datastore browser enables you to view all the datastores associated with the vSphere deployment, including all folders and files contained in them, such as virtual machine files. This is governed by the user permissions on VMware vCenter Server.</p> <p>In some cases, you might want to disable the datastore browser to eliminate the risk of having an open interface that is not being used.</p>
Threat	This is a Web interface and therefore has some of the general risks associated with all Web interfaces.
Recommendation Level	SSLF.

PARAMETER ELEMENT	DESCRIPTION
Parameter Setting	<p>To disable the datastore browser, edit the vpxd.cfg file and ensure that the following element is set:</p> <pre>&lt;enableHttpDatastoreAccess&gt;false&lt;/enableHttpDatastoreAccess&gt;</pre> <p>This should be the only occurrence of this element, and it should be within the &lt;vpxd&gt; ... &lt;/vpxd&gt; element in vpxd.cfg</p>
Effect on Functionality	<p>You will no longer be able to browse and view datastore files using a Web browser connected to VMware vCenter Server.</p> <p><i>NOTE: The datastore browser available on each VMware ESX/ESXi host is unaffected by this setting. It can be disabled separately using a host-level setting.</i></p>

### VMware vCenter Server Database

CONFIGURATION ELEMENT	DESCRIPTION
Code	VSD01
Name	Use least privileges for the VMware vCenter Server database user.
Description	VMware vCenter requires only certain specific privileges on the database. Furthermore, certain privileges are required only for installation and upgrade, and can be removed during normal operation. These privileges should be added again if another upgrade must be performed.
Risk or Control	Least privileges mitigates attacks if the VMware vCenter database account is compromised.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>The privileges needed for VMware vCenter on both Oracle and Microsoft SQL Server are given in the vSphere Upgrade Guide, "Preparing for the Upgrade to vCenter Server" chapter, "Prerequisites for the vCenter Server Upgrade" section, "Database Prerequisites" subsection. This document can be found here: <a href="http://www.vmware.com/pdf/vsphere4/r40_u1/vsp_40_u1_upgrade_guide.pdf">http://www.vmware.com/pdf/vsphere4/r40_u1/vsp_40_u1_upgrade_guide.pdf</a></p> <p><i>NOTE: This section indicates which privileges are needed for installation and upgrade, and which are needed just for ongoing operation.</i></p>



## VMware vSphere Client Components

Although SSL-based encryption is used to protect communication between client components and VMware vCenter Server or VMware ESX/ESXi, the Linux versions of these components do not perform certificate validation. Therefore, even if you have replaced the self-signed certificates on VMware vCenter and VMware ESX/ESXi with legitimate certificates signed by your local root certificate authority or a third party, communications with Linux clients are still vulnerable to MiTM attacks. The components that are vulnerable when running on Linux include:

- Any vCLI command
- Any vSphere SDK for Perl script
- Virtual machine console access initiated from a Linux-based vSphere Web Access browser session
- Any program written using the vSphere SDK

The management interfaces of VMware vCenter Server and VMware ESX should be available only on trusted networks, but providing encryption and certificate validation adds extra layers of defense against an attack. If you are able to militate against systems on the management network's interposing themselves on network traffic, or you can trust that such systems will not appear on the network, the use of Linux-based clients will not increase the security risk.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VCL01
Name	Restrict the use of Linux-based clients.
Description	Although SSL-based encryption is used to protect communication between client components and VMware vCenter Server or VMware ESX/ESXi, the Linux versions of these components do not perform certificate validation.
Risk or Control	<p>Even if you have replaced the self-signed certificates on VMware vCenter and VMware ESX/ESXi with legitimate certificates signed by your local root certificate authority or a third party, communications with Linux clients are still vulnerable to MiTM attacks.</p> <p>With proper controls, this restriction can be relaxed if deemed appropriate. These controls include:</p> <ul style="list-style-type: none"> <li>• Restriction of management network access only to authorized systems</li> <li>• Use of firewalls to restrict access to VMware vCenter only by authorized hosts</li> <li>• Use of jump-box systems for exclusive access to VMware vCenter</li> </ul>
Recommendation Level	DMZ.
Condition or Steps	<p>Options include:</p> <ul style="list-style-type: none"> <li>• Instruct administrators, especially those who have high levels of privileges, not to use Linux-based clients when connecting to VMware vCenter Server.</li> <li>• Make use of a jump-box architecture so that the only Linux clients are those behind the jump.</li> </ul>

VMware vCenter Server includes a vSphere Client extensibility framework, which provides the ability to extend the vSphere Client with menu selections or toolbar icons that provide access to VMware vCenter add-on components or external, Web-based functionality. With the flexibility, customization and innovation that this entails, there is also the risk of introducing vSphere Client capabilities that were not intended. For example, a plug-in might be surreptitiously installed on an administrator's vSphere Client instance, and then might execute arbitrary commands with the privilege level of that administrator. If a user with low or no privileges were to use such a client, there would be no added risk, because the plug-in can only interact with VMware vCenter or VMware ESX/ESXi with the permissions of the user running the client.

The integrity of client software is a common concern across all client-server platforms in which the client might be running on an insecure host, but the vSphere Client extensibility framework reduces the effort needed to compromise the client software. To protect against such compromises, users of vSphere Client should not install any plug-ins that do not come from a trusted source. You can check to see which plug-ins are actually installed for a given vSphere Client by going to the menu item **Plug-ins > Manage Plug-ins** and clicking the **Installed Plug-ins tab**.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VCL02
Name	Verify the integrity of vSphere Client.
Description	VMware vCenter Server includes a vSphere Client extensibility framework, which provides the ability to extend the vSphere Client with menu selections or toolbar icons that provide access to VMware vCenter Server add-on components or external, Web-based functionality.
Risk or Control	vSphere Client extensions run at the same privilege level as the user logged in. A malicious extension might masquerade as something useful but then do harmful things such as stealing credentials or misconfiguring the system.
Recommendation Level	Enterprise.
Condition or Steps	Make sure that the vSphere Client installation used by administrators includes only authorized extensions from trusted sources. You can check to see which plug-ins are actually installed for a given vSphere Client by going to the menu item <b>Plug-ins &gt; Manage Plug-ins</b> and clicking the <b>Installed Plug-ins tab</b> .

## VMware vCenter Update Manager

VMware vCenter includes a framework that enables you to add components to it that extend its functionality. These components typically run as separate services that are installed on a separate host or in a virtual machine. For the *VMware vSphere 4.1 Security Hardening Guide*, the only such component that is considered in-scope is VMware Update Manager. If you choose to make use of other add-on components, use the recommendations herein as a guide to how they should be deployed securely.

You should consider Update Manager an essential component of any VMware infrastructure deployment. The ability to make sure that critical operating system patches are applied to all virtual machines, especially offline virtual machines and templates, addresses one of the most important aspects of security in a virtualized environment. Furthermore, the ability to automate the patching of VMware ESX/ESXi hosts greatly increases the likelihood that you are protected against any vulnerability that might be discovered for this platform. Although there are numerous other ways to keep the virtual machine up to date with respect to patches, Update Manager is the preferred way to keep the VMware ESX/ESXi hosts patched.

In the default installation, the host where you install Update Manager also needs access to the Internet to download patches and patch information. You can configure it to use a Web proxy, a step you should take if a Web proxy is available. For highest security, you can install the VMware vCenter Update Manager Download Service on a separate server. The patches and information that it downloads can be transferred manually to the Update Manager host—for example, using a USB key or scheduled, secure file transfer. This prevents having the Update Manager host itself connected to an external network. For more information on installing Update Manager and the Update Manager Download Service, see the “Working with Update Manager” chapter in the **VMware Update Manager Administration Guide**.

CONFIGURATION ELEMENT	DESCRIPTION
Code	VUM01
Name	Use least privileges for the Update Manager database user.
Description	<p>Update Manager requires certain privileges on its database user in order to install, and the installer automatically checks for these. These are documented in the <i>VMware Update Manager Administration Guide</i>.</p> <p>However, after installation, only a small number of privileges are required for operation. The privileges on the VUM database user can be reduced during normal operation. These privileges should be added again if an upgrade or uninstall must be performed.</p>
Risk or Control	Least privileges mitigates attacks if the Update Manager database account is compromised.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>For Oracle: After installation, only the following permissions are needed for normal operation: <i>create session, create any table, drop any table</i>.</p> <p>For SQL Server: After installation, the <i>dba_owner</i> role or <i>sysadmin</i> role can be removed from the MSDB database (it is still required, however, for the Update Manager database).</p> <p>Please check the latest <i>VMware Update Manager Administration Guide</i> for any updates to these configurations.</p>

OPERATIONAL ELEMENT	DESCRIPTION
Code	VUM02
Name	Keep the Update Manager system properly patched.
Description	By staying up to date on Windows patches, vulnerabilities in the OS can be mitigated.
Risk or Control	If an attacker can obtain access and elevate privileges on the Update Manager system, it can compromise the patching process.
Recommendation Level	Enterprise.
Condition or Steps	Employ a system to keep the Update Manager system up to date with patches in accordance with industry-standard guidelines, or internal guidelines where appropriate.

OPERATIONAL ELEMENT	DESCRIPTION
Code	VUM03
Name	Provide Windows system protection on the Update Manager system.
Description	By providing OS-level protection, vulnerabilities in the OS can be mitigated.
Risk or Control	If an attacker can obtain access and elevate privileges on the Update Manager system, it can compromise the patching process.
Recommendation Level	Enterprise.
Condition or Steps	Provide Windows system protection, such as antivirus, in accordance with industry-standard guidelines, or internal guidelines where appropriate.
Code	VUM04
Name	Avoid user login to the Update Manager system.
Description	After someone has logged in to the Update Manager system, it becomes more difficult to prevent what they can do. In general, logging in to the Update Manager system should be limited to very privileged administrators, and then only for the purpose of administering Update Manager or the host OS.
Risk or Control	Anyone logged in to the Update Manager can potentially cause harm, either intentionally or unintentionally, by altering settings and modifying processes.
Recommendation Level	Enterprise.
Condition or Steps	Restrict login to the Update Manager to only those personnel who have legitimate tasks to perform in it. Ensure that they log in only when necessary, and audit these events.

CONFIGURATION ELEMENT	DESCRIPTION
Code	VUM05
Name	Do not configure Update Manager to manage its own virtual machine or the virtual machine of its VMware vCenter Server.
Description	Although you can install both Update Manager and VMware vCenter Server on virtual machines and place them on the same VMware ESX/ESXi host, you should not configure Update Manager to manage the patches on those virtual machines.
Risk or Control	Upon scanning and remediation, the virtual machine on which Update Manager and VMware vCenter Server are installed can reboot and the whole deployment system will shut down.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	If installed in virtual machines, ensure that Update Manager does not manage the patching of the virtual machine on which it runs, nor the virtual machine on which the associated VMware vCenter Server runs.

CONFIGURATION ELEMENT	DESCRIPTION
Code	VUM06
Name	Do not use default self-signed certificates.
Description	Self-signed certificates are automatically generated by Update Manager during the installation process, are not signed by a commercial CA, and might not provide strong security. Replace default self-signed certificates with those from a trusted certification authority, either a commercial CA or an organizational CA.
Risk or Control	The use of default certificates leaves the SSL connection open to MiTM attacks. Changing the default certificates to trusted CA-signed certificates mitigates the potential for MiTM attacks.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	For instructions on how to change self-signed certificates on Update Manager, see the following VMware knowledge base article: <a href="http://kb.vmware.com/kb/1023011">http://kb.vmware.com/kb/1023011</a> .

Update Manager has three main architectures for obtaining and registering patches:

- 1) Direct download onto the Update Manager system
- 2) Download onto a separate system and then network-based transfer via a Web server - this is referred to as a "semi-air-gap" model
- 3) Download onto a separate system, and then physical transfer via portable media - this is referred to as an "air-gap" model

Both the semi-air-gap and air-gap models make use of the Update Manager Download Service, which is a component that is installed on a separate, standalone system. It connects to public repositories, and downloads the patches. From that point, how the patches are transferred to the Update Manager system depends on the model being used.

For information on how to set up these alternatives, refer to the *VMware vCenter Update Manager Administration Guide*, in the "Installing, Setting Up, and Using Update Manager Download Service" chapter; as well as in the "Configuring Update Manager" chapter, "Configuring Update Manager Patch Download Sources" section.

CONFIGURATION ELEMENT	DESCRIPTION
Code	VUM10
Name	Limit the connectivity between Update Manager and public patch repositories.
Description	In a typical deployment, Update Manager connects to public patch repositories on the Internet to download patches. This connection should be limited as much as possible to prevent access from the outside to the Update Manager system.
Risk or Control	Any channel to the Internet represents a threat.
Recommendation Level	Enterprise.      DMZ.      SSLF.

CONFIGURATION ELEMENT	DESCRIPTION		
Parameters or Objects Configuration	Configure a Web proxy for Update Manager, rather than directly connecting to the Internet.	Configure Update Manager to use the Download Service, and configure a Web server to transfer the files to the Update Manager server (semi-air-gap model).	Configure Update Manager to use the Download Service, and use physical media to transfer the files to the Update Manager server (air-gap model).
Test	Check the proxy settings for Update Manager to make sure they are correct. Refer to the guide in the “Configuring Update Manager” chapter in the “Configure Update Manager Proxy Settings” section.	Ensure that the Download Service is functioning and that the Update Manager server does not obtain patches directly from the Internet.	Ensure that the Download Service is functioning and that the Update Manager server does not obtain patches directly from the Internet.

## Console Operating System (COS)

### Console Network Protection

VMware ESX includes a built-in firewall between the service console and the network. To ensure the integrity of the service console, VMware has limited the number of firewall ports that are open by default. At installation time, the service console firewall is configured to block all incoming and outgoing traffic except for ports 902, 443, 80 and 22, which are used for basic communication with VMware ESX. This setting enforces a high level of security for the VMware ESX host. Medium security blocks all incoming traffic except on the default ports (902, 443, 80 and 22) and any ports users specifically open. Outgoing traffic is not blocked. Low security does not block either incoming or outgoing traffic. This setting is equivalent to removing the firewall. Because the ports open by default on the VMware ESX are strictly limited, additional ports might need to be open after installation for third-party applications such as management, storage, NTP, and so on. For instance, a backup agent might use specific ports such as 13720, 13724, 13782 and 13783.

The list of ports used by VMware ESX can be found in this VMware knowledge base article: <http://kb.vmware.com/kb/1012382>.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	CON01
Name	Ensure that VMware ESX firewall is configured to high security.
Description	VMware ESX Server includes a built-in firewall between the service console and the network. A high-security setting disables all outbound traffic and allows only selected inbound traffic.
Risk or Control	Prevention of network-based exploits.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	The following commands configure high security on the firewall: esxcfg-firewall --blockIncoming esxcfg-firewall --blockOutgoing
Test	Ensure that outbound connections are blocked and only selected inbound connections are allowed.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	CON02
Name	Limit network access to applications and services.
Description	As a security best practice, disabling and removing services and applications that aren't required is advisable. The VMware ESX service console, by default, has a number of available services that should be disabled unless required for business. Also, ensure limited use of external software within the service console. Examples of additional software that might be acceptable to run in the service console are management and backup agents.  For more information and recommendations on running third-party software in the service console, see <a href="http://www.vmware.com/vmtr/resources/516">http://www.vmware.com/vmtr/resources/516</a> .

CONFIGURATION ELEMENT	DESCRIPTION
Risk or Control	Prevention of network-based exploits.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	All services not required explicitly for business purposes should be disabled.
Test	Run the “esxcfg-firewall –query” command to determine what services are enabled. To disable a service, execute the “esxcfg-firewall –d <service name>” command.

PARAMETER ELEMENT	DESCRIPTION
Code Number	CON03
Name	Do not run NFS or NIS clients in the service console.
Description	Because of the standards for how NFS and NIS are implemented, enabling the NFS or NIS client service in the service console opens up outbound UDP and TCP ports 0–65535; that is, it unblocks <b>all</b> outbound IPv4 connections.  <i>NOTE: Some implementations of NFS allow the server to configure specific ports for communication. These can then be selectively opened on the service console firewall, but not through the built-in services configuration.</i>
Risk or Control	Turning on these services effectively disables the service console firewall for outbound connections.
Recommendation Level	Enterprise.
Parameters Setting	Run the “esxcfg-firewall –query” command to determine whether nfsClient or nisClient is enabled. To disable a service, execute the “esxcfg-firewall –d <service name>” command.

## Console Management

Although the VMware ESX service console is derived from Red Hat Linux, it is a unique operating platform that should not be managed as a true Linux host. As such, the service console should be managed according to VMware and other virtualization security best practices, which might differ from many well-known Linux-focused best practices in some ways.

If you follow the best practice of isolating the network for the service console, there is no reason to run any antivirus or other such security agents, and their use is not necessarily recommended. However, if your environment requires that such agents be used, use a version designed to run on Red Hat Enterprise Linux 5.



OPERATIONAL ELEMENT	DESCRIPTION
Code Number	COM01
Name	Do not apply Red Hat patches to the service console.
Description	Although the VMware ESX service console is derived from Red Hat Linux, it is important that you not treat it like a Linux host when it comes to patching. Never apply patches issued by Red Hat or any other third-party vendor.
Risk or Control	The service console is generated from a Red Hat Linux distribution that has been modified to provide exactly the functionality necessary to communicate with and allow management of the VMkernel. Any additional software installed should not depend upon the presence of the standard set of RPM packages. In several cases, the packages that do exist have been modified especially for VMware ESX.
Recommendation Level	Enterprise.
Condition or Steps	Apply only patches that are published by VMware specifically for the versions of VMware ESX that you have in use. These are published for download periodically, as well as on an as-needed basis for security fixes. You can receive notifications for security-related patches by signing up for email notifications at <a href="http://www.vmware.com/security">http://www.vmware.com/security</a> .

OPERATIONAL ELEMENT	DESCRIPTION
Code Number	COM02
Name	Do not rely upon tools that check only for Red Hat patches.
Description	You should never use a scanner to analyze the security of the service console unless the scanner is specifically designed to work with your version of VMware ESX.
Risk or Control	Scanners that assume that the service console is a standard Red Hat Linux distribution routinely yield false positives. These scanners typically look only for strings in the names of software. They therefore do not account for the fact that VMware releases custom versions of packages with special names when providing security fixes. Because these special names are unknown to the scanners, they are flagged as vulnerabilities when in reality they are not.
Recommendation Level	Enterprise.
Condition or Steps	You should use only scanners that specifically treat the VMware ESX service console as a unique target. For more information, see the “Security Patches and Security Vulnerability Scanning Software” section in the “Service Console Security” chapter of the <i>VMware ESX Server 4 Configuration Guide</i> .

OPERATIONAL ELEMENT	DESCRIPTION
Code Number	COM03
Name	Do not manage the service console as a Red Hat Linux host.
Description	The usual redhat-config-* commands are not present, nor are other components such as the X server.
Risk or Control	Attempts to manage the service console as a typical Red Hat Linux host might result in misconfigurations that affect security, including availability.
Recommendation Level	Enterprise.
Condition or Steps	Manage the service console using purpose-built commands, such as vmkfstools and the esxcfg-* commands, to the extent possible, and only use other built-in commands as necessary. Do not deploy additional packages for management unless absolutely needed for a specific purpose.

OPERATIONAL ELEMENT	DESCRIPTION
Code Number	COM04
Name	Use vSphere Client and VMware vCenter Server to administer the hosts instead of service console.
Description	The best measure to prevent security incidents in the service console is to avoid accessing it if at all possible. You can perform many of the tasks necessary to configure and maintain the VMware ESX host using the vSphere Client, either connected directly to the host or, better yet, going through VMware vCenter Server. Another alternative is to use a remote scripting interface, such as vCLI or PowerCLI. These interfaces are built on the same API that vSphere Client and VMware vCenter Server use, so any script using them automatically enjoys the same benefits of authentication, authorization and auditing.
Risk or Control	By using alternatives to the service console, the need to access it is reduced, thereby minimizing the risk due to misuse.
Recommendation Level	Enterprise.
Condition or Steps	<p>Security policies and processes should be written that require the use of the remote API-based tools wherever possible. Accounts with direct service console access should be limited to the minimum number of administrators possible.</p> <p>Some advanced tasks, such as initial configuration for password policies, cannot be performed via the vSphere Client. For these tasks, you must log in to the service console. Also, if you lose your connection to the host, executing certain of these commands through the command line interface might be your only recourse—for example, if the network connection fails and you are therefore unable to connect using vSphere Client.</p>

## Console Password Policies

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COP01
Name	Use a directory service for authentication.
Description	<p>Advanced configuration and troubleshooting of a VMware ESX host might require local privileged access to the service console. For these tasks, you should set up individual host-localized user accounts and groups for the few administrators with overall responsibility for your virtual infrastructure. Ideally, these accounts should correspond to real individuals and not be accounts shared by multiple persons. Although you can create on the service console of each host local accounts that correspond to each global account, this presents the problem of having to manage user names and passwords in multiple places. It is much better to use a directory service, such as NIS or LDAP, to define and authenticate users on the service console, so you do not have to create local user accounts.</p> <p>If an organization does not rely upon the service console for configuration and routine operations, or if the number of individuals who are allowed to access the service console is small, the maintenance of local accounts will not present too large an overhead. In this case, a directory service might not be necessary. This decision should be dictated by local security policies.</p>
Risk or Control	Centralized control of user authentication greatly reduces the chance of misconfiguration or inappropriate access.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	See the <i>ESX Configuration Guide</i> , Chapter 13 "Authentication and User Management" for information on how to configure Active Directory for authentication: <a href="http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esx_server_config.pdf">http://www.vmware.com/pdf/vsphere4/r41/vsp_41_esx_server_config.pdf</a> .

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COP02
Name	Establish a password policy for password complexity.
Description	<p>These controls ensure that users create passwords that are hard for password generators to determine. Instead of using words, a common technique for ensuring password complexity is to use a memorable phrase, then derive a password from it—for example, by using the first letter of each word.</p> <p>The default pam_cracklib.so plug-in provides sufficient password strength enforcement for most environments. However, if the pam_cracklib.so plug-in is not stringent enough for your needs, you can change the parameters used for the pam_cracklib.so plug-in or use the pam_passwdqc.so plug-in instead. You can change the plug-in by using the esxcfg-auth-usepamqc command.</p>
Risk or Control	This recommendation addresses the risk of passwords' being guessed or cracked.
Recommendation Level	DMZ.

CONFIGURATION ELEMENT	DESCRIPTION
Parameters or Objects Configuration	<p><b>esxcfg-auth --usepamqc</b></p> <p>This command requires six parameters in the following order:</p> <ul style="list-style-type: none"> <li>• Minimum length of a single-character-class password</li> <li>• Minimum length of a password that has characters from two character classes</li> <li>• Minimum number of words in a passphrase</li> <li>• Minimum length of a password that has characters from three character classes</li> <li>• Minimum length of a password that has characters from four character classes</li> <li>• Maximum number of characters reused from the previous password</li> </ul> <p>If you pass a value of -1 for any of the six parameters, it disables that option. For example, the command line</p> <p><b>esxcfg-auth --usepamqc=-1 -1 -1 12 8 -1</b></p> <p>disables the first three parameters, requires a 12-character password using characters from three character classes or an 8-character password that uses characters from four character classes and disables the final parameter.</p>
Test	<p>Check the following line in the <b>/etc/pam.d/system-auth-generic file</b>:</p> <p><b>“password required /lib/security/\$ISA/pam_passwdqc.so”:</b></p> <p>If no text string is displayed, the complexity is not set. If there is a text string at the end of this line, ensure that it meets your policy.</p>

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COP03
Name	Establish a password policy for password history.
Description	Keeping a password history mitigates the risk of a user’s reusing a previously used password too often.
Risk or Control	This recommendation addresses the risk of passwords’ being guessed or cracked.
Recommendation Level	DMZ.
Parameters or Objects Configuration	<p>If it does not already exist, create a password history file:</p> <pre>touch /etc/security/opasswd chmod 600 /etc/security /opasswd</pre> <p>Set the number of passwords to retain for matching:</p> <p>Edit the <b>/etc/pam.d/system-auth</b> file and add the string “remember=x” to the end of the following line, where x is the number of passwords to retain:</p> <p>“password sufficient /lib/security/\$ISA/pam_unix.so”</p>
Test	Check for the presence of the string “remember=” and ensure that the value is in compliance with your internal policy.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COP04
Name	Establish a maximum password aging policy.
Description	These controls govern how long a user password can be active before the user is required to change it.
Risk or Control	They help ensure that passwords change often enough that if an attacker obtains a password through sniffing or social engineering, the attacker cannot continue to access the ESX host indefinitely.
Recommendation Level	DMZ.
Parameters or Objects Configuration	To set the maximum password age, use the following command:  <b>esxcfg-auth --passmaxdays=n</b>  where n is the maximum number of days for a password to live.
Test	Run the following command to see what the password maximum life setting is set to:  <b>grep -i max_days /etc/login.defs</b>  This number should be compared to your policy.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COP05
Name	Establish a password policy for minimum days before a password is changed.
Description	Because the maximum number of days for a password to live is important, there also must be a minimum number of days as well. This will mitigate the risk of a user's changing a password enough times to enable the reuse of their favorite password, which is outside of the password reuse policy.
Risk or Control	This recommendation addresses the risk of passwords' being guessed or cracked.
Recommendation Level	DMZ.
Parameters or Objects Configuration	<b>esxcfg-auth --passmindays=n</b>
Test	Run the following command to check the setting for password minimum life:  "grep -i min_days /etc/login.defs"  This number should be compared to your policy.

## Console Logging

Proper and thorough logging enables you to keep track of any unusual activity that might be a precursor to an attack. It also allows you to do a postmortem on any compromised systems and learn how to prevent attacks from occurring in the future.

The syslog daemon performs the system logging in VMware ESX. You can access the log files in the service console by going to the `/var/log/` directory. Several types of log files generated by VMware ESX are shown in the following table.

COMPONENT	LOCATION	PURPOSE
VMkernel	<code>/var/log/vmkernel</code>	Records activities related to the virtual machines and VMware ESX
VMkernel warnings	<code>/var/log/vmkwarning</code>	Records activities with the virtual machines
VMkernel summary	<code>/var/log/vmksummary</code>	Used to determine uptime and availability statistics for VMware ESX; comma separated
VMkernel summary human readable	<code>/var/log/vmksummary.txt</code>	Used to determine uptime and availability statistics for VMware ESX; human readable summary
VMware ESX host agent log	<code>/var/log/vmware/hostd.log</code>	Contains information on the agent that manages and configures the VMware ESX host and its virtual machines
vCenter agent	<code>/var/log/vmware/vpx/vpxa.log</code>	Contains information on the agent that communicates with VMware vCenter
Web access	Log all the files in the directory <code>/var/log/vmware/webAccess/*.log</code> : <code>client.log</code> , <code>proxy.log</code> , <code>unitTest.log</code> , <code>viewhelper.log</code> , <code>objectMonitor.log</code> , <code>timer.log</code> , <code>updateThread.log</code>	Records information on Web-based access to VMware ESX (service <code>vmware-webAccess</code> start on VMware ESX host to enable this)
Authentication log	<code>/var/log/secure</code>	Contains records of connections that require authentication, such as VMware daemons and actions initiated by the <code>xinetd</code>
Service console	<code>/var/log/messages</code>	Contains all general log messages used to troubleshoot virtual machines or VMware ESX
Virtual machines	The same directory as the affected virtual machine's configuration files; named <code>vmware.log</code> and <code>vmware*.log</code> , e.g: <code>/vmfs/volumes/&lt;datastore&gt;/&lt;virtual machine&gt;/vmware.log</code>	Contains virtual machine power events, system crashes, tools status and activity, time sync, virtual hardware changes, vMotion migrations, machine clones, and so on

The log files provide an important tool for diagnosing security breaches as well as other system issues. They also provide key sources of audit information. In addition to storing log information in files on the local file system, you can send this log information to a remote system. The syslog program is typically used for computer system management and security auditing, and it can serve these purposes well for VMware ESX hosts. You can select certain logs to be sent to a remote system.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COL01
Name	Configure syslog logging.
Description	Remote logging to a central host provides a way to greatly increase administration capabilities. By gathering log files onto a central host, you can easily monitor all hosts with a single tool as well as do aggregate analysis and searching to look for such things as coordinated attacks on multiple hosts.
Risk or Control	Logging to a secure, centralized log server can help prevent log tampering and provides a long-term audit record.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>Syslog operation is controlled by the configuration file <code>/etc/syslog.conf</code>. For logs you want to send to a remote log host, add a line with <code>@&lt;loghost.company.com&gt;</code> after the message type, where <code>&lt;loghost.company.com&gt;</code> is the name of a host configured to record remote log files. Make sure that this host name can be properly resolved, putting an entry in the name service maps if needed.</p> <p>Example:</p> <pre>local6.warning @&lt;loghost.company.com&gt;</pre> <p>After modifying the file, tell the syslog daemon to reread it by issuing the following command:</p> <pre>kill -SIGHUP `cat /var/run/syslogd.pid`</pre> <p>At a minimum, the following files should be logged to a remote syslog server:</p> <pre>/var/log/vmkernel /var/log/secure /var/log/messages /var/log/vmware/*.log /var/log/vmware/vpx/vpxa.log</pre>
Test	<p>To check that remote logging is configured:</p> <pre>cat /etc/syslog.conf   grep @</pre> <p>To check that remote logging traffic is permitted outbound from the host:</p> <pre>esxcfg-firewall -q   grep 514</pre> <p>To check that syslog service is configured to run:</p> <pre>chkconfig -list   grep syslog</pre>

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COL02
Name	Configure NTP time synchronization.
Description	By ensuring that all systems use the same relative time source (including the relevant localization offset), and that the relative time source can be correlated to an agreed-upon time standard (such as Coordinated Universal Time—UTC), you can make it simpler to track and correlate an intruder's actions when reviewing the relevant log files.
Risk or Control	Incorrect time settings might make it difficult to inspect and correlate log files to detect attacks and would make auditing inaccurate.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	NTP can be configured on a VMware ESX host using the vSphere Client, or using a remote command line interface such as vCLI or PowerCLI.
Test	<ul style="list-style-type: none"> <li>• Query the NTP configuration to make sure that a valid time source has been configured.</li> <li>• Make sure that the NTP service is running on the host.</li> </ul>

## Console Hardening

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COH01
Name	Partition the disk to prevent the root file system from filling up.
Description	<p>If the root file system fills up, it can seriously degrade the performance of VMware ESX management capabilities or even make them unresponsive.</p> <p>When you install VMware ESX 4.1, the default partitioning creates only three partitions. To protect against the root file system's filling up, you can create additional separate partitions for the directories /home, /tmp, and /var/log. These are all directories that have the potential to fill up. If they are not isolated from the root partition, you might experience a denial of service if the root partition is full and unable to accept any more writes. The "ESX Partitioning" chapter in the <i>ESX and vCenter Server Installation Guide</i> covers disk partitions in more detail:</p> <p><a href="http://pubs.vmware.com/vsphere-esx-4-1/install_guide/c_esx_partitioning.html">http://pubs.vmware.com/vsphere-esx-4-1/install_guide/c_esx_partitioning.html</a>.</p>
Risk or Control	Prevents a denial of service against the management of that host.
Recommendation Level	Enterprise.
Parameters or Objects Configuration	/etc/fstab
Test	Run the "df" command and ensure that the directories for /home, /tmp, and /var/log are mounted on their own partitions.



The service console has a number of files that specify its configurations. Editing these files can result in significant configuration changes, possibly including changes that can open the host to attack or exploitation. Most of these files are not normally edited by hand, although in some cases this might be necessary. The following is a list of service console configuration files that are particularly important.

```

/etc/profile
/etc/ssh/sshd_config
/etc/pam.d/system-auth
/etc/grub.conf
/etc/krb.conf
/etc/krb5.conf
/etc/krb.realms
/etc/login.defs
/etc/openldap/ldap.conf
/etc/nscd.conf
/etc/ntp
/etc/ntp.conf
/etc/passwd
/etc/group
/etc/nsswitch.conf
/etc/resolv.conf
/etc/sudoers
/etc/shadow

```

In addition, VMware ESX configuration files located in the /etc/vmware directory store all the VMkernel information.

OPERATIONAL ELEMENT	DESCRIPTION
Code Number	COH03
Name	Establish and maintain file system integrity.
Description	It is essential to monitor the integrity of certain critical system files within the VMware ESX service console. In addition, the permissions of numerous critical files should be configured to prevent unnecessary access from occurring.
Risk or Control	Direct tampering with configuration files might result in undetectable changes.
Recommendation Level	DMZ.
Condition or Steps	Configuration files, especially those listed, should be monitored for integrity and unauthorized tampering, using a commercial tool such as Tripwire, or by using a checksum tool such as sha1sum, which is included in the service console. These files should also be backed up regularly, either by using backup agents or by doing backups based on file copying.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COH04
Name	Ensure that permissions of important files and utility commands have not been changed from default.
Description	Various files and utilities are installed with particular file permissions to enable certain functionality without requiring unnecessary privilege levels for the user accessing them.
Risk or Control	Changing permissions from default on these important files can have an effect on the functionality of the VMware ESX host and might potentially cause these commands to not run properly and, as such, cause a denial of service.
Recommendation Level	DMZ.
Parameters or Objects Configuration	<p>The <code>/usr/sbin/esxcfg-*</code> commands, which are all installed by default with permissions 555.</p> <p>The log files discussed in the previous section, all of which have permissions 600, except for the directory <code>/var/log/vmware/webAccess</code>, which has permissions 755, and the virtual machine log files, which have permissions 644.</p> <p>Certain system commands that have the SUID bit. These commands are listed here: <a href="http://pubs.vmware.com/vsphere-esx-4-1/server_config/r_default_setuid_applications.html">http://pubs.vmware.com/vsphere-esx-4-1/server_config/r_default_setuid_applications.html</a>.</p> <p>For all of these files, the user and group owner should be root.</p>

## Console Access

PARAMETER ELEMENT	DESCRIPTION
Code Number	COA01
Name	Prevent tampering at boot time.
Description	A grub password can be used to prevent users from booting into single-user mode or passing options to the kernel during boot.
Threat	By passing in boot parameters, it might be possible to influence the host so that it performs improperly, perhaps in a manner that is hard to detect.
Recommendation Level	DMZ.
Parameter Setting	During the VMware ESX installation, the advanced option allows you to set a grub password. This can also be set by directly editing <code>/boot/grub/grub.conf</code> . See the "Installing VMware ESX" chapter in the <i>ESX and vCenter Server Installation Guide</i> for more details.
Effect on Functionality	Unless the password is entered, the server boots only the kernel with the default options.

PARAMETER ELEMENT	DESCRIPTION
Code Number	COA02
Name	Require authentication for single-user mode.
Description	Anyone with physical access can access the service console as root if a password is not set for single-user mode access.
Threat	When this recommendation is followed, if an attacker gains access to the console, they can log in only as an ordinary user and won't necessarily be able to escalate privilege level without additional effort.
Recommendation Level	SSLF.
Parameter Setting	Add the line --:S:wait:/sbin/sulogin to /etc/inittab
Effect on Functionality	If the root password is lost, there will be no way to access the system.

PARAMETER ELEMENT	DESCRIPTION
Code Number	COA03
Name	Ensure that root access via SSH is disabled.
Description	Because the root user of the service console has almost unlimited capabilities, securing this account is the most important step you can take to secure the VMware ESX host. By default, all insecure protocols, such as FTP, Telnet and HTTP, are disabled. Remote access via SSH is enabled, but not for the root account.
Threat	By allowing root access via SSH, the ability to audit who is executing commands or performing tasks is negated. It is preferable to require users to log in to the system using their own account, and then elevate privileges to perform tasks that require this, using "su" or "sudo."
Recommendation Level	Enterprise.
Parameter Setting	The line "PermitRootLogin" in the /etc/sshd_conf should be set to "no."
Effect on Functionality	The root user will not be able to log in via SSH.

PARAMETER ELEMENT	DESCRIPTION
Code Number	COA04
Name	Disallow console root login.
Description	<p>You can disallow root access, even on the console of the VMware ESX host—that is, when you log in using a screen and keyboard attached to the server itself, or to a remote session attached to the server’s console. This approach forces anyone who wants to access the system to first log in using a regular user account, then use <code>sudo</code> or <code>su</code> to perform tasks.</p> <p>The net effect is that administrators can continue to access the system, but they never have to log in as root. Instead, they use <code>sudo</code> to perform particular tasks or <code>su</code> to perform arbitrary commands.</p>
Threat	When this recommendation is followed, if an attacker gains access to the console, they can log in only as an ordinary user and won’t necessarily be able to escalate privilege level without additional effort.
Recommendation Level	SSLF.
Parameter Setting	<p>To prevent direct root login on the console, modify the file <code>/etc/securetty</code> to be empty. While logged in as root, enter the following command:</p> <pre>cat /dev/null &gt; /etc/securetty</pre> <p>You should first create a nonprivileged account on the host to enable logins. Otherwise, you might find yourself locked out of the host. This nonprivileged account should be a local account—that is, one that does not require remote authentication—so that if the network connection to the directory service is lost, access to the host is still possible. You can ensure this access by defining a local password for this account, using the <code>passwd</code> command.</p>
Effect on Functionality	After you do this, only nonprivileged accounts will be allowed to log in at the console. Root login at the console will no longer be possible.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COA05
Name	Limit access to the su command.
Description	Because <code>su</code> is such a powerful command, you should limit access to it. By default, only users who are members of the wheel group in the service console have permission to run <code>su</code> . If a user attempts to run <code>su -</code> to gain root privileges and that user is not a member of the wheel group, the <code>su -</code> attempt fails and the event is logged.
Threat	
Recommendation Level	Enterprise.

CONFIGURATION ELEMENT	DESCRIPTION
Parameters or Objects Configuration	<p>Besides controlling who has access to the su command, through the pluggable authentication module (PAM) infrastructure, you can specify what type of authentication is required to successfully execute the command. In the case of the su command, the relevant PAM configuration file is /etc/pam.d/su. To allow only members of the wheel group to execute the su command, and then only after authenticating with a password, find the line beginning with "auth required" and remove the leading pound sign (#) so it reads:</p> <p>"auth required /lib/security/\$ISA/pam_wheel.so use_uid"</p>

The sudo utility should be used to control which privileged commands users can run while logged in to the service console. Among the commands you should regulate are all of the esxcfg-\* commands as well as those that configure networking and other hardware on the VMware ESX host. You should decide which set of commands should be available to more junior administrators and which commands you should allow only senior administrators to execute. You can also use sudo to restrict access to the su command.

Use the following tips to help you configure sudo:

- Configure local and remote sudo logging (see "Maintain Proper Logging" on page 12).
- Create a special group, such as vi\_admins, and allow only members of that group to use sudo.
- Use sudo aliases to determine the authorization scheme, then add and remove users in the alias definitions instead of in the commands specification.
- Be careful to permit only the minimum of necessary operations to each user and alias. Permit very few users to run the su command, because su opens a shell that has full root privileges but is not auditable.
- If you have configured authentication using a directory service, sudo uses it by default for its own authentication. This performance is controlled by the /etc/pam.d/sudo file, on the line for auth. The default setting—service=system-auth—tells sudo to use whatever authentication scheme has been set globally using the esxcfg-auth command.
- Require users to enter their own passwords when performing operations. This is the default setting. Do not require the root password, because this presents a security risk, and do not disable password checking. In sudo, the authentication persists for a brief period of time before sudo asks for a password again.

For further information and guidelines for using sudo, see <http://www.gratisoft.us/sudo/>.

CONFIGURATION ELEMENT	DESCRIPTION
Code Number	COA06
Name	Configure and use sudo to control administrative access.
Description	The sudo utility should be used to control which privileged commands users can run while logged in to the service console.
Risk or Control	
Recommendation Level	Enterprise.
Parameters or Objects Configuration	<p>Parameters to be configured are in the /etc/sudoers file.</p> <p>Among the commands you should regulate are all of the esxcfg-* commands as well as those that configure networking and other hardware on the VMware ESX host. You should decide which set of commands should be available to more junior administrators and which commands you should allow only senior administrators to execute. You can also use sudo to restrict access to the su command. Because each situation will be different, each configuration will be different, so no specific guidance can be given here.</p>
Test	Check the configuration in the /etc/sudoers file and ensure that it meets your policy.

